



# MS3106F18-9PX Information

Heisener.com

**Part Number** MS3106F18-9PX **Manufacturer** ITT Cannon, LLC

**Category** Connectors, Interconnects

Circular Connectors

**Description** CONN PLUG 7 POS STRAIGHT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **MS3106F18-9PX Specifications**

Manufacturer Part Number         MS3106F18-9PX           Manufacturer         ITT Cannon, LLC           Category         Connectors, Interconnects           Package         -           Series         Military, MIL-DTL-5015, MS           Connector Type         Plug, Male Pins           Number of Positions         7           Shell Size - Insert         18-9           Shell Size, MIL         -           Mounting Type         Free Hanging (In-Line)           Termination         Solder Cup           Fastening Type         Threaded           Orientation         X           Ingress Protection         Environment Resistant           Shell Material, Finish         Aluminum Alloy, Olive Drab Cadmium Plated           Contact Finish         Silver           Features         Cable Clamp, Coupling Nut           Voltage - Rated         200 VAC, 250 VDC           Current Rating         22A, 41A	MB31001 10-71 X Specifications	
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-5015, MSConnector TypePlug, Male PinsNumber of Positions7Shell Size - Insert18-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable Clamp, Coupling NutVoltage - Rated200VAC, 250VDCCurrent Rating22A, 41A	Manufacturer Part Number	MS3106F18-9PX
Package-SeriesMilitary, MIL-DTL-5015, MSConnector TypePlug, Male PinsNumber of Positions7Shell Size - Insert18-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable Clamp, Coupling NutVoltage - Rated200VAC, 250VDCCurrent Rating22A, 41A	Manufacturer	ITT Cannon, LLC
Package - Military, MIL-DTL-5015, MS Connector Type Plug, Male Pins Number of Positions 7 Shell Size - Insert 18-9 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation X Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 200VAC, 250VDC Current Rating 22A, 41A	Category	Connectors, Interconnects
Series Military, MIL-DTL-5015, MS  Connector Type Plug, Male Pins  Number of Positions 7  Shell Size - Insert 18-9  Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation X  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Cable Clamp, Coupling Nut  Voltage - Rated 200VAC, 250VDC  Current Rating 22A, 41A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions7Shell Size - Insert18-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable Clamp, Coupling NutVoltage - Rated200VAC, 250VDCCurrent Rating22A, 41A	Package	-
Number of Positions  Shell Size - Insert  18-9  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Threaded  Orientation  X  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Cable Clamp, Coupling Nut  Voltage - Rated  200VAC, 250VDC  Current Rating  7  Insert  Ins	Series	Military, MIL-DTL-5015, MS
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Threaded  Orientation  X  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Cable Clamp, Coupling Nut  Voltage - Rated  200VAC, 250VDC  Current Rating  22A, 41A	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded Orientation X Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp, Coupling Nut Voltage - Rated 200VAC, 250VDC Current Rating 22A, 41A	Number of Positions	7
Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation X  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Cable Clamp, Coupling Nut  Voltage - Rated 200VAC, 250VDC  Current Rating 22A, 41A	Shell Size - Insert	18-9
Termination Solder Cup Fastening Type Threaded Orientation X Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 200VAC, 250VDC Current Rating 22A, 41A	Shell Size, MIL	-
Fastening Type  Orientation  X  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  Cable Clamp, Coupling Nut  Voltage - Rated  200VAC, 250VDC  Current Rating  Threaded  201  Current Rating  Threaded  X  Contact Finish  Environment Resistant  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Cable Clamp, Coupling Nut  200VAC, 250VDC	Mounting Type	Free Hanging (In-Line)
Orientation X Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 200VAC, 250VDC Current Rating 22A, 41A	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 200VAC, 250VDC Current Rating 22A, 41A	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Cable Clamp, Coupling Nut  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  Cable Clamp, Coupling Nut  200VAC, 250VDC  22A, 41A	Orientation	X
Contact Finish Silver Cable Clamp, Coupling Nut Voltage - Rated 200VAC, 250VDC Current Rating 22A, 41A	Ingress Protection	Environment Resistant
Features Cable Clamp, Coupling Nut  Voltage - Rated 200VAC, 250VDC  Current Rating 22A, 41A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 200VAC, 250VDC Current Rating 22A, 41A	Contact Finish	Silver
Current Rating 22A, 41A	Features	Cable Clamp, Coupling Nut
-	Voltage - Rated	200VAC, 250VDC
Report errors?	Current Rating	22A, 41A
		Report errors?

### MS3106F18-9PX Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### MS3106F18-9PX Payment Methods

































If you have any question about MS3106F18-9PX, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com