



MS3106F22-9P Information

Heisener.com

Part Number MS3106F22-9P

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 3POS INLINE PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3106F22-9P Specifications

Manufacturer Part Number MS3106F22-9P Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-5015 Connector Type Plug, Male Pins Number of Positions 3 Shell Size - Insert 22-9 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 1250VAC, 1750VDC Current Rating -		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-5015 Connector Type Plug, Male Pins Number of Positions 3 Shell Size - Insert 22-9 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated Urrent Rating - Connectors Military, MIL-DTL-5015 Plug, Male Pins Alluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Contact Finish L250VAC, 1750VDC Current Rating -	Manufacturer Part Number	MS3106F22-9P
Package-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Male PinsNumber of Positions3Shell Size - Insert22-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated1250VAC, 1750VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Male PinsNumber of Positions3Shell Size - Insert22-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated1250VAC, 1750VDCCurrent Rating-	Category	Connectors, Interconnects
Series Military, MIL-DTL-5015 Connector Type Plug, Male Pins Number of Positions 3 Shell Size - Insert 22-9 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 1250VAC, 1750VDC Current Rating		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions3Shell Size - Insert22-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated1250VAC, 1750VDCCurrent Rating-	Package	-
Number of Positions Shell Size - Insert 22-9 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated Current Rating -	Series	Military, MIL-DTL-5015
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 1250VAC, 1750VDC Current Rating -	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 1250VAC, 1750VDC Current Rating	Number of Positions	3
Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 1250VAC, 1750VDC Current Rating -	Shell Size - Insert	22-9
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 1250VAC, 1750VDC Current Rating -	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 1250VAC, 1750VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 1250VAC, 1750VDC Current Rating -	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 1250VAC, 1750VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 1250VAC, 1750VDC Current Rating -	Orientation	N (Normal)
Contact Finish Silver Features Strain Relief Voltage - Rated 1250VAC, 1750VDC Current Rating -	Ingress Protection	Environment Resistant
Features Strain Relief Voltage - Rated 1250VAC, 1750VDC Current Rating -	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 1250VAC, 1750VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	Strain Relief
	Voltage - Rated	1250VAC, 1750VDC
Report errors?	Current Rating	-
1		Report errors?

MS3106F22-9P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3106F22-9P Payment Methods



















MS3106F22-9P Shipping Methods













If you have any question about MS3106F22-9P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com