



MS3106F28-21PZ Information

Heisener.com

Part Number MS3106F28-21PZ

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 37POS STRAIGHT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3106F28-21PZ Specifications

Manufacturer Part Number MS3106F28-21PZ Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-5015 Connector Type Plug, Male Pins Number of Positions 37 Shell Size - Insert 28-21 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating - Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Male PinsNumber of Positions37Shell Size - Insert28-21Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationZIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer Part Number	MS3106F28-21PZ
Package-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Male PinsNumber of Positions37Shell Size - Insert28-21Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationZIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package - Military, MIL-DTL-5015 Connector Type Plug, Male Pins Number of Positions 37 Shell Size - Insert 28-21 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Category	Connectors, Interconnects
Series Military, MIL-DTL-5015 Connector Type Plug, Male Pins Number of Positions 37 Shell Size - Insert 28-21 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions37Shell Size - Insert28-21Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationZIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Package	-
Number of Positions37Shell Size - Insert28-21Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationZIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Series	Military, MIL-DTL-5015
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating	Number of Positions	37
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationZIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Shell Size - Insert	28-21
Termination Solder Cup Fastening Type Threaded Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver Strain Relief	Orientation	Z
Contact Finish Features Strain Relief Voltage - Rated Current Rating Silver Strain Relief	Ingress Protection	Environment Resistant
Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	Strain Relief
-	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
		Report errors?

MS3106F28-21PZ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3106F28-21PZ Payment Methods



















MS3106F28-21PZ Shipping Methods













If you have any question about MS3106F28-21PZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com