



## MS3106R18-6S Information

Heisener.com

Part Number MS3106R18-6S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 1POS INLINE SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **MS3106R18-6S Specifications**

Manufacturer Part Number     MS3106R18-6S       Manufacturer     Amphenol Industrial Operations       Category     Connectors, Interconnects       Package     -       Series     Military, MIL-DTL-5015       Connector Type     Plug, Female Sockets       Number of Positions     1       Shell Size - Insert     18-6       Shell Size, MIL     -       Mounting Type     Free Hanging (In-Line)       Termination     Solder Cup       Fastening Type     Threaded       Orientation     N (Normal)       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum Alloy, Olive Drab Cadmium Plated       Contact Finish     Silver       Features     Strain Relief       Voltage - Rated     900VAC, 1250VDC       Current Rating     -		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Female SocketsNumber of Positions1Shell Size - Insert18-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Manufacturer Part Number	MS3106R18-6S
Package-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Female SocketsNumber of Positions1Shell Size - Insert18-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Female SocketsNumber of Positions1Shell Size - Insert18-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-5015Connector TypePlug, Female SocketsNumber of Positions1Shell Size - Insert18-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions1Shell Size - Insert18-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Package	-
Number of Positions  Shell Size - Insert  18-6  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Strain Relief  Voltage - Rated  900VAC, 1250VDC  Current Rating  -	Series	Military, MIL-DTL-5015
Shell Size - Insert Shell Size, MIL	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated 900VAC, 1250VDC  Current Rating	Number of Positions	1
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Shell Size - Insert	18-6
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating -	Termination	Solder Cup
Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Strain Relief  Voltage - Rated 900VAC, 1250VDC  Current Rating -	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  Ourrent Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  Strain Relief	Orientation	N (Normal)
Contact Finish Silver  Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating -	Ingress Protection	Environment Resistant
Features Strain Relief  Voltage - Rated 900VAC, 1250VDC  Current Rating -	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 900VAC, 1250VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	Strain Relief
-	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	-
		Report errors

#### MS3106R18-6S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### MS3106R18-6S Payment Methods



















# MS3106R18-6S Shipping Methods













If you have any question about MS3106R18-6S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com