



### MS3106R32-17P Information

Heisener.com

Part Number MS3106R32-17P Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 4POS INLINE W/PINS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# MS3106R32-17P Specifications

Manufacturer Part Number       MS3106R32-17P         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       Military, MIL-DTL-5015, MS         Connector Type       Plug, Male Pins         Number of Positions       4         Shell Size - Insert       32-17         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Solder Cup         Fastening Type       Threaded         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       Backshell, Coupling Nut         Voltage - Rated       900VAC, 1250VDC         Current Rating       135A	•	
Category Circular Connectors  Package Package Series Military, MIL-DTL-5015, MS Connector Type Plug, Male Pins Number of Positions 4 Shell Size - Insert 32-17 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell, Coupling Nut Voltage - Rated	Manufacturer Part Number	MS3106R32-17P
Circular Connectors  Package - Series Military, MIL-DTL-5015, MS Connector Type Plug, Male Pins Number of Positions 4 Shell Size - Insert 32-17 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Backshell, Coupling Nut Voltage - Rated	Manufacturer	ITT Cannon, LLC
Package - Military, MIL-DTL-5015, MS  Connector Type Plug, Male Pins  Number of Positions 4  Shell Size - Insert 32-17  Shell Size, MIL - Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Backshell, Coupling Nut  Voltage - Rated	Category	Connectors, Interconnects
Series Military, MIL-DTL-5015, MS  Connector Type Plug, Male Pins  Number of Positions 4  Shell Size - Insert 32-17  Shell Size, MIL		Circular Connectors
Connector Type Plug, Male Pins Number of Positions 4 Shell Size - Insert 32-17 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell, Coupling Nut Voltage - Rated	Package	-
Number of Positions  Shell Size - Insert  32-17  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  Backshell, Coupling Nut  Voltage - Rated  900VAC, 1250VDC	Series	Military, MIL-DTL-5015, MS
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Backshell, Coupling Nut  Voltage - Rated  32-17  Shell Manuminum Alloy  Solder Cup  Threaded  N (Normal)  Environment Resistant  Sliver  Backshell, Coupling Nut  Voltage - Rated	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Backshell, Coupling Nut  Voltage - Rated 900VAC, 1250VDC	Number of Positions	4
Mounting Type Free Hanging (In-Line)  Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell, Coupling Nut Voltage - Rated Protection Solder Cup Threaded Threaded N (Normal) Solder Cup Threaded N (Normal) Solder Cup Threaded N (Normal) Solder Cup Threaded Solder Cup Threaded Solder Cup Threaded N (Normal) Solder Cup Threaded Solder Cup Threaded Solder Cup	Shell Size - Insert	32-17
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell, Coupling Nut Voltage - Rated 900VAC, 1250VDC	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  Backshell, Coupling Nut  Voltage - Rated  900VAC, 1250VDC	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell, Coupling Nut Voltage - Rated 900VAC, 1250VDC	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell, Coupling Nut Voltage - Rated 900VAC, 1250VDC	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Backshell, Coupling Nut  Voltage - Rated  900VAC, 1250VDC	Orientation	N (Normal)
Contact Finish Silver Features Backshell, Coupling Nut Voltage - Rated 900VAC, 1250VDC	Ingress Protection	Environment Resistant
Features Backshell, Coupling Nut Voltage - Rated 900VAC, 1250VDC	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 900VAC, 1250VDC	Contact Finish	Silver
-	Features	Backshell, Coupling Nut
Current Rating 135A	Voltage - Rated	900VAC, 1250VDC
Curront runing	Current Rating	135A
Report errors?		Report errors?

### MS3106R32-17P Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MS3106R32-17P Payment Methods



















## MS3106R32-17P Shipping Methods













If you have any question about MS3106R32-17P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com