



MS3108A24-9P Information

Heisener.com

Part Number MS3108A24-9P

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 2POS RT ANG W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3108A24-9P Specifications

Manufacturer Part Number MS3108A24-9P Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series MIL-5015 Type Connector Type Plug, Male Pins Number of Positions 2 Shell Size - Insert 24-9 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating - Report errors?			
Category Connectors, Interconnects Circular Connectors Package - Series MIL-5015 Type Connector Type Plug, Male Pins Number of Positions 2 Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Manufacturer Part Number	MS3108A24-9P	
Circular Connectors Package - Series MIL-5015 Type Connector Type Plug, Male Pins Number of Positions 2 Shell Size - Insert 24-9 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Manufacturer	Amphenol Industrial Operations	
Package - Series MIL-5015 Type Connector Type Plug, Male Pins Number of Positions 2 Shell Size - Insert 24-9 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Voltage - Rated 500VAC, 700VDC Current Rating -	Category	Connectors, Interconnects	
Series MIL-5015 Type Connector Type Plug, Male Pins Number of Positions 2 Shell Size - Insert 24-9 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -		Circular Connectors	
Connector Type Plug, Male Pins Number of Positions 2 Shell Size - Insert 24-9 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Package	-	
Number of Positions Shell Size - Insert 24-9 Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated 500VAC, 700VDC Current Rating -	Series	MIL-5015 Type	
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated 500VAC, 700VDC Current Rating -	Connector Type	Plug, Male Pins	
Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Number of Positions	2	
Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size - Insert	24-9	
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-	
Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Mounting Type	Free Hanging (In-Line), Right Angle	
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Solder Cup	
Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Fastening Type	Threaded	
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating - Aluminum Alloy, Olive Drab Cadmium Plated Silver	Orientation	N (Normal)	
Contact Finish Features Voltage - Rated Current Rating Silver - - - - - - - - - - - - -	Ingress Protection	-	
Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated	
Voltage - Rated 500VAC, 700VDC Current Rating -	Contact Finish	Silver	
Current Rating -	Features	-	
	Voltage - Rated	500VAC, 700VDC	
Report errors?	Current Rating	-	
		Report errors	?

MS3108A24-9P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3108A24-9P Payment Methods





















MS3108A24-9P Shipping Methods













If you have any question about MS3108A24-9P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com