



# MS3108E14S-6S Information

Heisener.com

Part Number MS3108E14S-6S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

**Description** CONN PLUG 6POS RT ANG W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# MS3108E14S-6S Specifications

Manufacturer Part Number       MS3108E14S-6S         Manufacturer       Amphenol Industrial Operations         Category       Connectors, Interconnects         Circular Connectors         Package       -         Series       MIL-5015 Type         Connector Type       Plug, Female Sockets         Number of Positions       6         Shell Size - Insert       14S-6         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line), Right Angle         Termination       Solder Cup         Fastening Type       Threaded         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       -         Voltage - Rated       200VAC, 250VDC         Current Rating       -         Report errors?		
Category Connectors, Interconnects Circular Connectors  Package - Series MIL-5015 Type Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated Current Rating - Connectors, Interconnects Circular Connectors  NIL-5015 Type Plug, Female Sockets  Number of Position  6 Nometic Fire Hanging (In-Line), Right Angle Pree Hanging (In-Li	Manufacturer Part Number	MS3108E14S-6S
Circular Connectors  Package - Series MIL-5015 Type Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Manufacturer	Amphenol Industrial Operations
Package - MIL-5015 Type Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Woltage - Rated 200VAC, 250VDC Current Rating -	Category	Connectors, Interconnects
Series MIL-5015 Type Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating -		Circular Connectors
Connector Type Plug, Female Sockets  Number of Positions 6  Shell Size - Insert 14S-6  Shell Size, MIL -  Mounting Type Free Hanging (In-Line), Right Angle  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features -  Voltage - Rated 200VAC, 250VDC  Current Rating -	Package	-
Number of Positions  Shell Size - Insert  14S-6  Shell Size, MIL  Mounting Type  Free Hanging (In-Line), Right Angle  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  -  Voltage - Rated  200VAC, 250VDC  Current Rating  -	Series	MIL-5015 Type
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line), Right Angle  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  -  Voltage - Rated  200VAC, 250VDC  Current Rating  -	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line), Right Angle  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Number of Positions	6
Mounting Type Free Hanging (In-Line), Right Angle  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features -  Voltage - Rated 200VAC, 250VDC  Current Rating -	Shell Size - Insert	14S-6
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Mounting Type	Free Hanging (In-Line), Right Angle
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Termination	Solder Cup
Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features -  Voltage - Rated 200VAC, 250VDC  Current Rating -	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  -  Current Rating	Orientation	N (Normal)
Contact Finish Silver  Features - Voltage - Rated Current Rating - Silver -	Ingress Protection	Environment Resistant
Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 200VAC, 250VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
-	Voltage - Rated	200VAC, 250VDC
Report errors?	Current Rating	-
		Report errors?

#### MS3108E14S-6S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### MS3108E14S-6S Payment Methods



















# MS3108E14S-6S Shipping Methods













If you have any question about MS3108E14S-6S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com