



MS3108E16-10S Information

Heisener.com

Part Number MS3108E16-10S Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 3 POS RT ANG W/SCKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3108E16-10S Specifications

Manufacturer Part NumberMS3108E16-10SManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-5015, MSConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert16-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable Clamp, Coupling NutVoltage - Rated500VAC, 700VDCCurrent Rating41A	Wission in the specifications	
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-5015, MSConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert16-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable Clamp, Coupling NutVoltage - Rated500VAC, 700VDCCurrent Rating41A	Manufacturer Part Number	MS3108E16-10S
Package-SeriesMilitary, MIL-DTL-5015, MSConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert16-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable Clamp, Coupling NutVoltage - Rated500VAC, 700VDCCurrent Rating41A	Manufacturer	ITT Cannon, LLC
Package - Series Military, MIL-DTL-5015, MS Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert 16-10 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 41A	Category	Connectors, Interconnects
Series Military, MIL-DTL-5015, MS Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert 16-10 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 41A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert16-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable Clamp, Coupling NutVoltage - Rated500VAC, 700VDCCurrent Rating41A	Package	-
Number of Positions3Shell Size - Insert16-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable Clamp, Coupling NutVoltage - Rated500VAC, 700VDCCurrent Rating41A	Series	Military, MIL-DTL-5015, MS
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 41A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 41A	Number of Positions	3
Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable Clamp, Coupling NutVoltage - Rated500VAC, 700VDCCurrent Rating41A	Shell Size - Insert	16-10
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 41A	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 41A	Mounting Type	Free Hanging (In-Line), Right Angle
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 41A	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 41A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Cable Clamp, Coupling Nut Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver Cable Clamp, Coupling Nut 41A	Orientation	N (Normal)
Contact Finish Silver Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 41A	Ingress Protection	Environment Resistant
Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 41A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating 41A	Contact Finish	Silver
Current Rating 41A	Features	Cable Clamp, Coupling Nut
•	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	41A
		Report errors?

MS3108E16-10S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3108E16-10S Payment Methods



















MS3108E16-10S Shipping Methods













If you have any question about MS3108E16-10S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com