



MS3108E18-19S Information

Heisener.com

Part Number MS3108E18-19S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 10POS INLINE SKT RA

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3108E18-19S Specifications

Manufacturer Part NumberMS3108E18-19SManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMIL-5015 TypeConnector TypePlug, Female SocketsNumber of Positions10Shell Size - Insert18-19Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-Report errors?	Wissions Specifications	
Category Connectors, Interconnects Circular Connectors Package - Series MIL-5015 Type Connector Type Plug, Female Sockets Number of Positions 10 Shell Size - Insert 18-19 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated Current Rating -	Manufacturer Part Number	MS3108E18-19S
Package-SeriesMIL-5015 TypeConnector TypePlug, Female SocketsNumber of Positions10Shell Size - Insert18-19Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package - MIL-5015 Type Connector Type Plug, Female Sockets Number of Positions 10 Shell Size - Insert 18-19 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating	Category	Connectors, Interconnects
Series MIL-5015 Type Connector Type Plug, Female Sockets Number of Positions 10 Shell Size - Insert 18-19 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -		Circular Connectors
Connector Type Plug, Female Sockets Number of Positions 10 Shell Size - Insert 18-19 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Package	-
Number of Positions Shell Size - Insert 18-19 Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated Current Rating -	Series	MIL-5015 Type
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating	Number of Positions	10
Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size - Insert	18-19
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating	Mounting Type	Free Hanging (In-Line), Right Angle
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver Strain Relief	Orientation	N (Normal)
Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Ingress Protection	Environment Resistant
Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	Strain Relief
•	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
		Report errors?

MS3108E18-19S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3108E18-19S Payment Methods



















MS3108E18-19S Shipping Methods













If you have any question about MS3108E18-19S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com