



MS3108E24-10P Information

Heisener.com

Part Number MS3108E24-10P Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 7POS RT ANG W/PINS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3108E24-10P Specifications

Manufacturer Part Number MS3108E24-10P Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series Military, MIL-DTL-5015, MS Connector Type Plug, Male Pins Number of Positions 7 Shell Size - Insert 24-10 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 74A		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-5015, MSConnector TypePlug, Male PinsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable Clamp, Coupling NutVoltage - Rated500VAC, 700VDCCurrent Rating74A	Manufacturer Part Number	MS3108E24-10P
Circular Connectors Package - Series Military, MIL-DTL-5015, MS Connector Type Plug, Male Pins Number of Positions 7 Shell Size - Insert 24-10 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 74A	Manufacturer	ITT Cannon, LLC
Package-SeriesMilitary, MIL-DTL-5015, MSConnector TypePlug, Male PinsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable Clamp, Coupling NutVoltage - Rated500VAC, 700VDCCurrent Rating74A	Category	Connectors, Interconnects
Series Military, MIL-DTL-5015, MS Connector Type Plug, Male Pins Number of Positions 7 Shell Size - Insert 24-10 Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 74		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable Clamp, Coupling NutVoltage - Rated500VAC, 700VDCCurrent Rating74A	Package	-
Number of Positions Shell Size - Insert 24-10 Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 74A	Series	Military, MIL-DTL-5015, MS
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 74A	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 74A	Number of Positions	7
Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 74A	Shell Size - Insert	24-10
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 74A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 74A	Mounting Type	Free Hanging (In-Line), Right Angle
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 74A	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 74A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 74A	Orientation	N (Normal)
Contact Finish Silver Cable Clamp, Coupling Nut Voltage - Rated Current Rating 74A	Ingress Protection	Environment Resistant
Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 74A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating 74A	Contact Finish	Silver
Current Rating 74A	Features	Cable Clamp, Coupling Nut
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	74A
		Report errors?

MS3108E24-10P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3108E24-10P Payment Methods





















MS3108E24-10P Shipping Methods













If you have any question about MS3108E24-10P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com