



### **MS3111E14-12P Information**

Heisener.com

Part Number MS3111E14-12P

Manufacturer Amphenol Industrial Operations

**Category** Connectors, Interconnects

Circular Connectors

**Description** CONN RCPT 12POS CBL MNT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **MS3111E14-12P Specifications**

Manufacturer Part Number  Manufacturer  Amphenol Industrial Operations  Category  Connectors, Interconnects  Circular Connectors  Package  Series  Military, MIL-DTL-26482 Series I, PT  Connector Type  Receptacle, Male Pins  Number of Positions  12  Shell Size - Insert  14-12  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Gold  Features  Voltage - Rated  600VAC  Current Rating  7.5A, 13A		
Category Connectors, Interconnects Circular Connectors  Package - Series Military, MIL-DTL-26482 Series I, PT Connector Type Receptacle, Male Pins Number of Positions 12 Shell Size - Insert 14-12 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Manufacturer Part Number	MS3111E14-12P
Circular Connectors  Package - Series Military, MIL-DTL-26482 Series I, PT Connector Type Receptacle, Male Pins Number of Positions 12 Shell Size - Insert 14-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Manufacturer	Amphenol Industrial Operations
Package - Military, MIL-DTL-26482 Series I, PT Connector Type Receptacle, Male Pins Number of Positions 12 Shell Size - Insert 14-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Category	Connectors, Interconnects
Series Military, MIL-DTL-26482 Series I, PT Connector Type Receptacle, Male Pins Number of Positions 12 Shell Size - Insert 14-12 Shell Size, MIL		Circular Connectors
Connector Type Receptacle, Male Pins Number of Positions 12 Shell Size - Insert 14-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Package	-
Number of Positions  Shell Size - Insert  14-12  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Gold  Features  -  Voltage - Rated  600VAC  Current Rating  7.5A, 13A	Series	Military, MIL-DTL-26482 Series I, PT
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Features  -  Voltage - Rated  600VAC  Current Rating  7.5A, 13A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold  Features Voltage - Rated 600VAC Current Rating 7.5A, 13A	Number of Positions	12
Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Gold  Features -  Voltage - Rated 600VAC  Current Rating 7.5A, 13A	Shell Size - Insert	14-12
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Shell Size, MIL	-
Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Gold  Features  -  Voltage - Rated  600VAC  Current Rating  7.5A, 13A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Termination	Solder Cup
Ingress Protection  Environment Resistant  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Gold  Features  Voltage - Rated  Current Rating  Environment Resistant  Aluminum, Olive Drab Cadmium Plated  Gold  7.5A, 13A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  Voltage - Rated  Current Rating  Aluminum, Olive Drab Cadmium Plated  Gold  Gold  7.5A, 13A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 600VAC Current Rating 7.5A, 13A	Contact Finish	Gold
Current Rating 7.5A, 13A	Features	-
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A, 13A
		Report errors?

#### **MS3111E14-12P Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MS3111E14-12P Payment Methods



















### MS3111E14-12P Shipping Methods













If you have any question about MS3111E14-12P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com