



MS3114E22-41S Information

Heisener.com

Part Number MS3114E22-41S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 41POS JAM NUT W/SCKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3114E22-41S Specifications

Manufacturer Part Number MS3114E22-41S Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 41 Shell Size - Insert 22-41 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 41 Shell Size - Insert 22-41 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated Convert Rating 7,5A, 13A	Manufacturer Part Number	MS3114E22-41S
Package-SeriesMilitary, MIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions41Shell Size - Insert22-41Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A, 13A	Manufacturer	Amphenol Industrial Operations
Package - Military, MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 41 Shell Size - Insert 22-41 Shell Size, MIL - Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7, 55, 13A	Category	Connectors, Interconnects
Series Military, MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 41 Shell Size - Insert 22-41 Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions41Shell Size - Insert22-41Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A, 13A	Package	-
Number of Positions41Shell Size - Insert22-41Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A, 13A	Series	Military, MIL-DTL-26482 Series I, PT
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Number of Positions	41
Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A, 13A	Shell Size - Insert	22-41
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Gold	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 600VAC Current Rating 7.5A, 13A	Contact Finish	Gold
Current Rating 7.5A, 13A	Features	-
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A, 13A
		Report errors?

MS3114E22-41S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3114E22-41S Payment Methods



















MS3114E22-41S Shipping Methods













If you have any question about MS3114E22-41S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com