



# MS3114F14-12S Information

Heisener.com

Part Number MS3114F14-12S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

**Description** CONN RCPT 12POS JAM NUT W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# MS3114F14-12S Specifications

Manufacturer Part Number       MS3114F14-12S         Manufacturer       Amphenol Industrial Operations         Category       Connectors, Interconnects         Package       -         Series       Military, MIL-DTL-26482 Series I, PT         Connector Type       Receptacle, Female Sockets         Number of Positions       12         Shell Size - Insert       14-12         Shell Size, MIL       -         Mounting Type       Panel Mount, Bulkhead - Front Side Nut         Termination       Solder Cup         Fastening Type       Bayonet Lock         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Olive Drab Cadmium Plated         Contact Finish       Gold         Features       Strain Relief         Voltage - Rated       600VAC         Current Rating       7.5A, 13A         Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A	Manufacturer Part Number	MS3114F14-12S
Package-SeriesMilitary, MIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A	Manufacturer	Amphenol Industrial Operations
Package - Military, MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 12 Shell Size - Insert 14-12 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7, 7.5A, 13A	Category	Connectors, Interconnects
Series Military, MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 12 Shell Size - Insert 14-12 Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A	Package	-
Number of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A	Series	Military, MIL-DTL-26482 Series I, PT
Shell Size - Insert  Shell Size, MIL  Mounting Type  Panel Mount, Bulkhead - Front Side Nut  Termination  Solder Cup  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Gold  Features  Strain Relief  Voltage - Rated  600VAC  Current Rating  7.5A, 13A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Solder Cup  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Features Strain Relief  Voltage - Rated 600VAC Current Rating 7.5A, 13A	Number of Positions	12
Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Solder Cup  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief  Voltage - Rated 600VAC Current Rating 7.5A, 13A	Shell Size - Insert	14-12
Termination Solder Cup  Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  Strain Relief  Voltage - Rated  Current Rating  Aluminum, Olive Drab Cadmium Plated  Gold  Contact Finish  Gold  Strain Relief  7.5A, 13A	Orientation	N (Normal)
Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A	Ingress Protection	Environment Resistant
Features Strain Relief  Voltage - Rated 600VAC  Current Rating 7.5A, 13A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 600VAC Current Rating 7.5A, 13A	Contact Finish	Gold
Current Rating 7.5A, 13A	Features	Strain Relief
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A, 13A
		Report errors?

#### MS3114F14-12S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MS3114F14-12S Payment Methods





















## MS3114F14-12S Shipping Methods













If you have any question about MS3114F14-12S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com