



MS3114P20-39S Information

Heisener.com

Part Number MS3114P20-39S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects
Circular Connectors

Circular Connectors

Description CONN RCPT 39POS JAM NUT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3114P20-39S Specifications

Manufacturer Part NumberMS3114P20-39SManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions39Shell Size - Insert20-39Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesPottedVoltage - Rated600VACCurrent Rating7.5A, 13AReport errors?		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions39Shell Size - Insert20-39Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesPottedVoltage - Rated600VACCurrent Rating7.5A, 13A	Manufacturer Part Number	MS3114P20-39S
Circular Connectors Package - Series Military, MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 39 Shell Size - Insert 20-39 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted Voltage - Rated Convac Current Rating 7,5A, 13A	Manufacturer	Amphenol Industrial Operations
Package - Military, MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 39 Shell Size - Insert 20-39 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7, 7.5A, 13A	Category	Connectors, Interconnects
Series Military, MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 39 Shell Size - Insert 20-39 Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions39Shell Size - Insert20-39Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesPottedVoltage - Rated600VACCurrent Rating7.5A, 13A	Package	-
Number of Positions39Shell Size - Insert20-39Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesPottedVoltage - Rated600VACCurrent Rating7.5A, 13A	Series	Military, MIL-DTL-26482 Series I, PT
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Potted Voltage - Rated Current Rating 7.5A, 13A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A	Number of Positions	39
Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesPottedVoltage - Rated600VACCurrent Rating7.5A, 13A	Shell Size - Insert	20-39
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A	Termination	Solder Cup
Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Potted Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Gold Potted 7.5A, 13A	Orientation	N (Normal)
Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A	Ingress Protection	-
Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 600VAC Current Rating 7.5A, 13A	Contact Finish	Gold
Current Rating 7.5A, 13A	Features	Potted
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A, 13A
		Report errors?

MS3114P20-39S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3114P20-39S Payment Methods



















MS3114P20-39S Shipping Methods













If you have any question about MS3114P20-39S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com