



MS3114P24-61S Information

Heisener.com

Part Number MS3114P24-61S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 61POS JAM NUT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3114P24-61S Specifications

Manufacturer Part Number MS3114P24-61S Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 61 Shell Size - Insert 24-61 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions61Shell Size - Insert24-61Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesPottedVoltage - Rated600VACCurrent Rating7.5A	Manufacturer Part Number	MS3114P24-61S
Circular Connectors Package - Series Military, MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 61 Shell Size - Insert 24-61 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted Voltage - Rated Convac Current Rating 7,5A	Manufacturer	Amphenol Industrial Operations
Package - Military, MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 61 Shell Size - Insert 24-61 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7,5A	Category	Connectors, Interconnects
Series Military, MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 61 Shell Size - Insert 24-61 Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions61Shell Size - Insert24-61Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesPottedVoltage - Rated600VACCurrent Rating7.5A	Package	-
Number of Positions61Shell Size - Insert24-61Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesPottedVoltage - Rated600VACCurrent Rating7.5A	Series	Military, MIL-DTL-26482 Series I, PT
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Potted Voltage - Rated 600VAC Current Rating 7.5A	Number of Positions	61
Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesPottedVoltage - Rated600VACCurrent Rating7.5A	Shell Size - Insert	24-61
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A	Termination	Solder Cup
Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Potted Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Gold Potted 7.5A	Orientation	N (Normal)
Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	-
Features Potted Voltage - Rated 600VAC Current Rating 7.5A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	Potted
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

MS3114P24-61S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3114P24-61S Payment Methods



















MS3114P24-61S Shipping Methods













If you have any question about MS3114P24-61S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com