



## MS3126F10-6SX Information

Heisener.com

Part Number MS3126F10-6SX

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects **Circular Connectors** 

**Description** CONN PLUG 6POS STRAIGHT W/SCKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# MS3126F10-6SX Specifications

Manufacturer Part Number       MS3126F10-6SX         Manufacturer       Amphenol Industrial Operations         Category       Connectors, Interconnects         Package       -         Series       Military, MIL-DTL-26482 Series I, PT         Connector Type       Plug, Female Sockets         Number of Positions       6         Shell Size - Insert       10-6         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       X         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Olive Drab Cadmium Plated         Contact Finish       Gold         Features       Strain Relief         Voltage - Rated       600VAC         Current Rating       7.5A		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert10-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A	Manufacturer Part Number	MS3126F10-6SX
Package-SeriesMilitary, MIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert10-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A	Manufacturer	Amphenol Industrial Operations
Package-SeriesMilitary, MIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert10-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A	Category	Connectors, Interconnects
Series Military, MIL-DTL-26482 Series I, PT Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 10-6 Shell Size, MIL		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert10-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A	Package	-
Number of Positions6Shell Size - Insert10-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A	Series	Military, MIL-DTL-26482 Series I, PT
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  X  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Gold  Features  Strain Relief  Voltage - Rated  Courrent Rating  7.5A	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Bayonet Lock Orientation X Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Number of Positions	6
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A	Shell Size - Insert	10-6
Termination Crimp Fastening Type Bayonet Lock Orientation X Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type  Orientation  X  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Gold  Features  Strain Relief  Voltage - Rated  600VAC  Current Rating  7.5A	Mounting Type	Free Hanging (In-Line)
Orientation X Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating 7.5A	Orientation	X
Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features Strain Relief  Voltage - Rated 600VAC  Current Rating 7.5A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	Strain Relief
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

### MS3126F10-6SX Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MS3126F10-6SX Payment Methods



















## MS3126F10-6SX Shipping Methods













If you have any question about MS3126F10-6SX, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com