



MS3126F14-15SW Information

Heisener.com

Part Number MS3126F14-15SW

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects
Circular Connectors

Description CONN PLUG 15POS STRAIGHT W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3126F14-15SW Specifications

| Manufacturer Part NumberMS3126F14-15SWManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions15Shell Size - Insert14-15Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600 VACCurrent Rating7.5A, 13AReport errors? | | |
|---|--------------------------|--------------------------------------|
| CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions15Shell Size - Insert14-15Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A | Manufacturer Part Number | MS3126F14-15SW |
| Circular Connectors Package - Series Military, MIL-DTL-26482 Series I, PT Connector Type Plug, Female Sockets Number of Positions 15 Shell Size - Insert 14-15 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated Current Rating 7.5A, 13A | Manufacturer | Amphenol Industrial Operations |
| Package-SeriesMilitary, MIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions15Shell Size - Insert14-15Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A | Category | Connectors, Interconnects |
| Series Military, MIL-DTL-26482 Series I, PT Connector Type Plug, Female Sockets Number of Positions 15 Shell Size - Insert 14-15 Shell Size, MIL | | Circular Connectors |
| Connector TypePlug, Female SocketsNumber of Positions15Shell Size - Insert14-15Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A | Package | - |
| Number of Positions15Shell Size - Insert14-15Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A | Series | Military, MIL-DTL-26482 Series I, PT |
| Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating 7.5A, 13A | Connector Type | Plug, Female Sockets |
| Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A | Number of Positions | 15 |
| Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A | Shell Size - Insert | 14-15 |
| Termination Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A | Shell Size, MIL | - |
| Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A | Mounting Type | Free Hanging (In-Line) |
| Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A | Termination | Crimp |
| Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A | Fastening Type | Bayonet Lock |
| Shell Material, Finish Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Gold Contact Finish Gold Strain Relief 7.5A, 13A | Orientation | W |
| Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A | Ingress Protection | Environment Resistant |
| Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A | Shell Material, Finish | Aluminum, Olive Drab Cadmium Plated |
| Voltage - Rated 600VAC Current Rating 7.5A, 13A | Contact Finish | Gold |
| Current Rating 7.5A, 13A | Features | Strain Relief |
| | Voltage - Rated | 600VAC |
| Report errors? | Current Rating | 7.5A, 13A |
| | | Report errors? |

MS3126F14-15SW Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3126F14-15SW Payment Methods



















MS3126F14-15SW Shipping Methods













If you have any question about MS3126F14-15SW, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com