



# MS3126P12-10S Information

Heisener.com

Part Number MS3126P12-10S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 10POS STRAIGHT W/SCKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# MS3126P12-10S Specifications

| Manufacturer Part Number     MS3126P12-10S       Manufacturer     Amphenol Industrial Operations       Category     Connectors, Interconnects       Package     -       Series     Military, MIL-DTL-26482 Series I, PT       Connector Type     Plug, Female Sockets       Number of Positions     10       Shell Size - Insert     12-10       Shell Size, MIL     -       Mounting Type     Free Hanging (In-Line)       Termination     Crimp       Fastening Type     Bayonet Lock       Orientation     N (Normal)       Ingress Protection     -       Shell Material, Finish     Aluminum, Olive Drab Cadmium Plated       Contact Finish     Gold       Features     -       Voltage - Rated     600VAC       Current Rating     7.5A |                          |                                      |
|--|--------------------------|--------------------------------------|
| CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A   | Manufacturer Part Number | MS3126P12-10S                        |
| Circular Connectors  Package - Series Military, MIL-DTL-26482 Series I, PT Connector Type Plug, Female Sockets Number of Positions 10 Shell Size - Insert 12-10 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated Courrent Rating 7.5A  | Manufacturer             | Amphenol Industrial Operations       |
| Package-SeriesMilitary, MIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A  | Category                 | Connectors, Interconnects            |
| Series Military, MIL-DTL-26482 Series I, PT Connector Type Plug, Female Sockets Number of Positions 10 Shell Size - Insert 12-10 Shell Size, MIL   |                          | Circular Connectors                  |
| Connector TypePlug, Female SocketsNumber of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A  | Package                  | -                                    |
| Number of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A  | Series                   | Military, MIL-DTL-26482 Series I, PT |
| Shell Size - Insert12-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A   | Connector Type           | Plug, Female Sockets                 |
| Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Features - Voltage - Rated 600VAC Current Rating 7.5A   | Number of Positions      | 10                                   |
| Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A   | Shell Size - Insert      | 12-10                                |
| Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7,5A   | Shell Size, MIL          | -                                    |
| Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A   | Mounting Type            | Free Hanging (In-Line)               |
| Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A   | Termination              | Crimp                                |
| Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A  | Fastening Type           | Bayonet Lock                         |
| Shell Material, Finish  Contact Finish  Gold  Features  - Voltage - Rated  Current Rating  Aluminum, Olive Drab Cadmium Plated  Gold  600VAC  7.5A   | Orientation              | N (Normal)                           |
| Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A  | Ingress Protection       | -                                    |
| Features - Voltage - Rated 600VAC Current Rating 7.5A  | Shell Material, Finish   | Aluminum, Olive Drab Cadmium Plated  |
| Voltage - Rated 600VAC Current Rating 7.5A   | Contact Finish           | Gold                                 |
| Current Rating 7.5A  | Features                 | -                                    |
|  | Voltage - Rated          | 600VAC                               |
| Report errors?   | Current Rating           | 7.5A                                 |
|  |                          | Report errors?                       |

#### MS3126P12-10S Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# MS3126P12-10S Payment Methods



















### MS3126P12-10S Shipping Methods













If you have any question about MS3126P12-10S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com