



MS3456KT16S-8S Information

Heisener.com

Part Number MS3456KT16S-8S

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 5POS STRAIGHT W/SCKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3456KT16S-8S Specifications

Manufacturer Part Number Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-5015 Connector Type Plug, Female Sockets Number of Positions 5 Shell Size - Insert 16S-8 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Contact Finish Gold Features Voltage - Rated - Current Rating 13A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-5015 Connector Type Plug, Female Sockets Number of Positions 5 Shell Size - Insert 16S-8 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Steel, Olive Drab Cadmium Plated Contact Finish Gold Features Voltage - Rated - Connectors, Interconnects Circular Connectors Hilderonectors All Hilderonectors Military, MIL-DTL-5015 Flug, Female Sockets Nelly, Female Sockets Nelly Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Fluid Resistant Shell Material, Finish Steel, Olive Drab Cadmium Plated Contact Finish Gold Features Firewall Usage Voltage - Rated	Manufacturer Part Number	MS3456KT16S-8S
Package-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert16S-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionFluid ResistantShell Material, FinishSteel, Olive Drab Cadmium PlatedContact FinishGoldFeaturesFirewall UsageVoltage - Rated-	Manufacturer	Amphenol Aerospace Operations
Package-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert16S-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionFluid ResistantShell Material, FinishSteel, Olive Drab Cadmium PlatedContact FinishGoldFeaturesFirewall UsageVoltage - Rated-	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-5015Connector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert16S-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionFluid ResistantShell Material, FinishSteel, Olive Drab Cadmium PlatedContact FinishGoldFeaturesFirewall UsageVoltage - Rated-		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert16S-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionFluid ResistantShell Material, FinishSteel, Olive Drab Cadmium PlatedContact FinishGoldFeaturesFirewall UsageVoltage - Rated-	Package	-
Number of Positions5Shell Size - Insert16S-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionFluid ResistantShell Material, FinishSteel, Olive Drab Cadmium PlatedContact FinishGoldFeaturesFirewall UsageVoltage - Rated-	Series	Military, MIL-DTL-5015
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Steel, Olive Drab Cadmium Plated Contact Finish Gold Features Voltage - Rated 16S-8 Free Hanging (In-Line) Strimp Threaded Orientation N (Normal) Fluid Resistant Steel, Olive Drab Cadmium Plated Contact Finish Gold Free Hanging (In-Line) Threaded Orientation N (Normal) Fluid Resistant Steel, Olive Drab Cadmium Plated	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Fluid Resistant Shell Material, Finish Steel, Olive Drab Cadmium Plated Contact Finish Gold Features Firewall Usage Voltage - Rated -	Number of Positions	5
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionFluid ResistantShell Material, FinishSteel, Olive Drab Cadmium PlatedContact FinishGoldFeaturesFirewall UsageVoltage - Rated-	Shell Size - Insert	16S-8
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Fluid Resistant Shell Material, Finish Steel, Olive Drab Cadmium Plated Contact Finish Gold Features Firewall Usage Voltage - Rated -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Fluid Resistant Shell Material, Finish Steel, Olive Drab Cadmium Plated Contact Finish Gold Features Firewall Usage Voltage - Rated Threaded N (Normal) Fluid Resistant Steel, Olive Drab Cadmium Plated Gold -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Fluid Resistant Shell Material, Finish Steel, Olive Drab Cadmium Plated Contact Finish Gold Features Firewall Usage Voltage - Rated -	Termination	Crimp
Ingress Protection Shell Material, Finish Steel, Olive Drab Cadmium Plated Contact Finish Gold Features Firewall Usage Voltage - Rated	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features Firewall Usage Voltage - Rated Steel, Olive Drab Cadmium Plated Gold	Orientation	N (Normal)
Contact Finish Gold Features Firewall Usage Voltage - Rated -	Ingress Protection	Fluid Resistant
Features Firewall Usage Voltage - Rated -	Shell Material, Finish	Steel, Olive Drab Cadmium Plated
Voltage - Rated -	Contact Finish	Gold
	Features	Firewall Usage
Current Rating 13A	Voltage - Rated	-
Current Nating 13A	Current Rating	13A
Report errors?		Report errors?

MS3456KT16S-8S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3456KT16S-8S Payment Methods



















MS3456KT16S-8S Shipping Methods













If you have any question about MS3456KT16S-8S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com