



## MS3459L36-3PW Information

Heisener.com

Part Number MS3459L36-3PW

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 6POS STRAIGHT PINS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# MS3459L36-3PW Specifications

| Manufacturer Part Number       MS3459L36-3PW         Manufacturer       Amphenol Aerospace Operations         Category       Connectors, Interconnects         Package       -         Series       Military, MIL-DTL-5015         Connector Type       Plug, Male Pins         Number of Positions       6         Shell Size - Insert       36-3         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Crimp         Fastening Type       Threaded         Orientation       W         Ingress Protection       Fluid Resistant         Shell Material, Finish       Aluminum, Nickel Plated, Electroless         Contact Finish       Gold         Features       Self Locking         Voltage - Rated       -         Current Rating       23A, 150A   |                          |                                      |
|---|--------------------------|--------------------------------------|
| Category Connectors, Interconnects Circular Connectors  Package - Series Military, MIL-DTL-5015 Connector Type Plug, Male Pins Number of Positions 6 Shell Size - Insert 36-3 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation W Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated Urrent Rating 23A, 150A  | Manufacturer Part Number | MS3459L36-3PW                        |
| Package-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Male PinsNumber of Positions6Shell Size - Insert36-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationWIngress ProtectionFluid ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating23A, 150A   | Manufacturer             | Amphenol Aerospace Operations        |
| Package - Series Military, MIL-DTL-5015 Connector Type Plug, Male Pins Number of Positions 6 Shell Size - Insert 36-3 Shell Size, MIL - Characteristics Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation W Ingress Protection Fluid Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Self Locking Voltage - Rated Current Rating 23A, 150A  | Category                 | Connectors, Interconnects            |
| Series Military, MIL-DTL-5015  Connector Type Plug, Male Pins  Number of Positions 6  Shell Size - Insert 36-3  Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Threaded  Orientation W  Ingress Protection Fluid Resistant  Shell Material, Finish Aluminum, Nickel Plated, Electroless  Contact Finish Gold  Features Self Locking  Voltage - Rated  Current Rating 23A, 150A  |                          | Circular Connectors                  |
| Connector TypePlug, Male PinsNumber of Positions6Shell Size - Insert36-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationWIngress ProtectionFluid ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating23A, 150A   | Package                  | -                                    |
| Number of Positions6Shell Size - Insert36-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationWIngress ProtectionFluid ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating23A, 150A  | Series                   | Military, MIL-DTL-5015               |
| Shell Size - Insert36-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationWIngress ProtectionFluid ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating23A, 150A  | Connector Type           | Plug, Male Pins                      |
| Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Crimp Fastening Type Threaded Orientation W Ingress Protection Fluid Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features Self Locking Voltage - Rated Current Rating  - Current Rating  - Carrent Self Size, MIL - Crimp Free Hanging (In-Line)  W Crimp Gold Crimp Corimp Corimp Corimp Corimp Free Hanging (In-Line)  Aluminum Ocity Corimp | Number of Positions      | 6                                    |
| Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Threaded  Orientation W  Ingress Protection Fluid Resistant  Shell Material, Finish Aluminum, Nickel Plated, Electroless  Contact Finish Gold  Features Self Locking  Voltage - Rated -  Current Rating 23A, 150A   | Shell Size - Insert      | 36-3                                 |
| Termination Crimp Fastening Type Threaded Orientation W Ingress Protection Fluid Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Self Locking Voltage - Rated Current Rating 23A, 150A   | Shell Size, MIL          | -                                    |
| Fastening Type  Orientation  W  Ingress Protection  Shell Material, Finish  Contact Finish  Contact Finish  Features  Self Locking  Voltage - Rated  Current Rating  Threaded  Threaded  Threaded  Threaded  Threaded  Threaded  Auminum, Nickel Plated, Electroless  Cold  Self Locking  23A, 150A   | Mounting Type            | Free Hanging (In-Line)               |
| Orientation W Ingress Protection Fluid Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Self Locking Voltage - Rated - Current Rating 23A, 150A   | Termination              | Crimp                                |
| Ingress Protection  Shell Material, Finish  Contact Finish  Gold  Features  Self Locking  Voltage - Rated  Current Rating  Fluid Resistant  Aluminum, Nickel Plated, Electroless  Gold  23A, 150A   | Fastening Type           | Threaded                             |
| Shell Material, Finish  Contact Finish  Gold  Features  Self Locking  Voltage - Rated  Current Rating  Aluminum, Nickel Plated, Electroless  Gold  Self Locking   | Orientation              | W                                    |
| Contact Finish Gold Features Self Locking  Voltage - Rated - Current Rating 23A, 150A   | Ingress Protection       | Fluid Resistant                      |
| Features Self Locking  Voltage - Rated - Current Rating 23A, 150A   | Shell Material, Finish   | Aluminum, Nickel Plated, Electroless |
| Voltage - Rated - Current Rating - 23A, 150A  | Contact Finish           | Gold                                 |
| Current Rating 23A, 150A  | Features                 | Self Locking                         |
|   | Voltage - Rated          | -                                    |
| Report errors?  | Current Rating           | 23A, 150A                            |
|   |                          | Report errors?                       |

### MS3459L36-3PW Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# MS3459L36-3PW Payment Methods



















## MS3459L36-3PW Shipping Methods













If you have any question about MS3459L36-3PW, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com