



MS3459L36-3SW Information

Heisener.com

Part Number MS3459L36-3SW

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 6POS STRAIGHT SCKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3459L36-3SW Specifications

Manufacturer Part Number MS3459L36-3SW Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-5015 Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 36-3 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation W Ingress Protection Fluid Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Self Locking Voltage - Rated - Current Rating 23A, 150A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-5015 Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 36-3 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation W Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated - Current Rating 23A, 150A	Manufacturer Part Number	MS3459L36-3SW
Package-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert36-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationWIngress ProtectionFluid ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating23A, 150A	Manufacturer	Amphenol Aerospace Operations
Package - Series Military, MIL-DTL-5015 Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 36-3 Shell Size, MIL - Characteristic Pree Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation W Ingress Protection Fluid Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Self Locking Voltage - Rated Current Rating 23A, 150A	Category	Connectors, Interconnects
Series Military, MIL-DTL-5015 Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 36-3 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation W Ingress Protection Fluid Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Self Locking Voltage - Rated Current Rating 23A, 150A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert36-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationWIngress ProtectionFluid ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating23A, 150A	Package	-
Number of Positions6Shell Size - Insert36-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationWIngress ProtectionFluid ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating23A, 150A	Series	Military, MIL-DTL-5015
Shell Size - Insert36-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationWIngress ProtectionFluid ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating23A, 150A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation W Ingress Protection Fluid Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features Self Locking Voltage - Rated Current Rating - Current Rating - Carrent Self Size, MIL - Crimp Free Hanging (In-Line) W Crimp Gold Crimp Corimp Corimp Corimp Corimp Free Hanging (In-Line) Aluminum Ocity Corimp	Number of Positions	6
Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation W Ingress Protection Fluid Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Self Locking Voltage - Rated - Current Rating 23A, 150A	Shell Size - Insert	36-3
Termination Crimp Fastening Type Threaded Orientation W Ingress Protection Fluid Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Self Locking Voltage - Rated Current Rating 23A, 150A	Shell Size, MIL	-
Fastening Type Orientation W Ingress Protection Shell Material, Finish Contact Finish Contact Finish Features Self Locking Voltage - Rated Current Rating Threaded Threaded Threaded Threaded Threaded Auminum, Nickel Plated, Electroless Cold Self Locking 23A, 150A	Mounting Type	Free Hanging (In-Line)
Orientation W Ingress Protection Fluid Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Self Locking Voltage - Rated - Current Rating 23A, 150A	Termination	Crimp
Ingress Protection Shell Material, Finish Contact Finish Gold Features Self Locking Voltage - Rated Current Rating Fluid Resistant Aluminum, Nickel Plated, Electroless Gold 23A, 150A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features Self Locking Voltage - Rated Current Rating Aluminum, Nickel Plated, Electroless Gold Self Locking	Orientation	W
Contact Finish Gold Features Self Locking Voltage - Rated - Current Rating 23A, 150A	Ingress Protection	Fluid Resistant
Features Self Locking Voltage - Rated - Current Rating 23A, 150A	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated - Current Rating - 23A, 150A	Contact Finish	Gold
Current Rating 23A, 150A	Features	Self Locking
	Voltage - Rated	-
Report errors?	Current Rating	23A, 150A
		Report errors?

MS3459L36-3SW Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3459L36-3SW Payment Methods



















MS3459L36-3SW Shipping Methods













If you have any question about MS3459L36-3SW, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com