

MS3459LS22-2P

a Quote

MS3459LS22-2P Information

Heisener.com	Part Number	MS3459LS22-2P	
	Manufacturer	Amphenol Aerospace Operations	
	Category	Connectors, Interconnects Circular Connectors	눤
	Description	CONN PLUG 3POS STRAIGHT PINS	- 39
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		US Websites https://www.bsises.com	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Requ

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MS3459LS22-2P Specifications

Manufacturer Part Number MS3459LS22-2P Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Package - Series Military, MIL-DTL-5015 Connector Type Plug, Male Pins Number of Positions 3 Shell Size - Insert 22-2 Mounting Type Free Hanging (In-Line) Termination Crimp Astening Type Threaded Orientation N(Normal) Ingress Protection Stailess steel Contact Finish Gold Fatures Self Locking Voltage - Rated -		
CategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Male PinsNumber of Positions3Shell Size - Insert22-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionStainless SteelShell Material, FinishSelf LockingVoltage - Rated-Cortart FinishSelf LockingVoltage - Rated-Kettade-StartesSelf LockingVoltage - Rated-Current Rating46A	Manufacturer Part Number	MS3459LS22-2P
Initial ConnectorsPackage-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Male PinsNumber of Positions3Shell Size - Insert22-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionStainless SteelShell Material, FinishSelf LockingFeaturesSelf LockingVoltage - Rated-Current Rating66A	Manufacturer	Amphenol Aerospace Operations
Package-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Male PinsNumber of Positions3Shell Size - Insert22-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeHreadedOrientationN(Normal)Ingress ProtectionStailess SteelShell Material, FinishGoldFeaturesSelf LockingVoltage - Rated-Kurent Rating64A	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-5015Connector TypePlug, Male PinsNumber of Positions3Shell Size - Insert22-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN(Normal)Ingress ProtectionStainless SteelShell Material, FinishGoldContact FinishSelf LockingVoltage - Rated-Ketter SteelSelf LockingStenter SteelSelf LockingStenter Steel-Stenter SteelSelf LockingStenter SteelSelf Lo		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions3Shell Size - Insert22-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionStainless SteelShell Material, FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating46A	Package	-
Number of Positions3Shell Size - Insert22-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionStainless SteelShell Material, FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating46A	Series	Military, MIL-DTL-5015
Shell Size - Insert22-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionFluid ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating46A	Connector Type	Plug, Male Pins
Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN(Normal)Ingress ProtectionFluid ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating64A	Number of Positions	3
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedForentationN (Normal)OrientationFluid ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating6A	Shell Size - Insert	22-2
TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionFluid ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating46A	Shell Size, MIL	-
Fastening TypeThreadedOrientationN (Normal)Ingress ProtectionFluid ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating46A	Mounting Type	Free Hanging (In-Line)
OrientationN (Normal)Ingress ProtectionFluid ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating46A	Termination	Crimp
Ingress ProtectionFluid ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating46A	Fastening Type	Threaded
Shell Material, FinishStainless SteelContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating46A	Orientation	N (Normal)
Contact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating46A	Ingress Protection	Fluid Resistant
FeaturesSelf LockingVoltage - Rated-Current Rating6A	Shell Material, Finish	Stainless Steel
Voltage - Rated-Current Rating46A	Contact Finish	Gold
Current Rating 46A	Features	Self Locking
-	Voltage - Rated	-
Report errors?	Current Rating	46A
		Report errors?

MS3459LS22-2P Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3459LS22-2P Payment Methods





If you have any question about MS3459LS22-2P, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com