

MS3459LS24-10PW

MS3459LS24-10PW Information

Heisener.com	 MS3459LS24-10PW Amphenol Aerospace Operations Connectors, Interconnects Circular Connectors CONN PLUG 7POS STRAIGHT PINS - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MS3459LS24-10PW Specifications

CategoryConnectors, InterconnectsCategoryCircular ConnectorsPackage-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Male PinsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationKuIngress ProtectionFluid ResistantShell Material, FinishGold		
CategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Male PinsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationWIngress ProtectionFluid ResistantShell Material, FinishStainless SteelContact FinishSelf LockingVoltage - Rated-Voltage - Rated-Current Rating46A	Manufacturer Part Number	MS3459LS24-10PW
Circular ConnectorsPackage-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Male PinsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationWIngress ProtectionStainless SteelShell Material, FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating64	Manufacturer	Amphenol Aerospace Operations
Package-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Male PinsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mouting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationFuid ResistantShell Material, FinishStainless SteelShell Material, FinishGoldYoltage - RatedSelf LockingVoltage - RatedSelf LockingYoltage - Rated46A	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-5015Connector TypePlug, Male PinsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeMuOrientationWIngress ProtectionFluid ResistantShell Material, FinishStainless SteelContact FinishSelf LockingVoltage - Rated-Yotage - Yotage -		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationWIngress ProtectionFuid ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating46A	Package	-
Number of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationWIngress ProtectionFuid ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating46A	Series	Military, MIL-DTL-5015
Shell Size - Insert24-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationWIngress ProtectionFuid ResistantShell Material, FinishStainless SteelContact FinishSelf LockingFeaturesSelf LockingVoltage - Rated-Current Rating60A	Connector Type	Plug, Male Pins
Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationWIngress ProtectionFluid ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf LockingVoltage - Rated-Kenter Steel-Shell Material, SteelStell SteelSteelStell SteelSteelStell Steel <td>Number of Positions</td> <td>7</td>	Number of Positions	7
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationWOrientationFuid ResistantIngress ProtectionStainless SteelShell Material, FinishGoldContact FinishSelf LockingYoltage - Rated-Current Rating6A	Shell Size - Insert	24-10
TerminationCrimpFastening TypeThreadedOrientationWIngress ProtectionFluid ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating46A	Shell Size, MIL	-
Fastening TypeThreadedFastening TypeWOrientationFluid ResistantIngress ProtectionStainless SteelShell Material, FinishGoldContact FinishSelf LockingFeaturesSelf LockingVoltage - Rated-Current Rating46A	Mounting Type	Free Hanging (In-Line)
OrientationWIngress ProtectionFluid ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating46A	Termination	Crimp
Ingress ProtectionFluid ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating46A	Fastening Type	Threaded
Shell Material, FinishStainless SteelContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating46A	Orientation	W
Contact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating46A	Ingress Protection	Fluid Resistant
FeaturesSelf LockingVoltage - Rated-Current Rating46A	Shell Material, Finish	Stainless Steel
Voltage - Rated-Current Rating46A	Contact Finish	Gold
Current Rating 46A	Features	Self Locking
	Voltage - Rated	-
Report errors?	Current Rating	46A
		Report errors?

MS3459LS24-10PW Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3459LS24-10PW Payment Methods





If you have any question about MS3459LS24-10PW, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com