

# MS3459LS40-1S

#### MS3459LS40-1S Information

Contract territors	MS3459LS40-1S Amphenol Aerospace Operations Connectors, Interconnects Circular Connectors CONN PLUG 30POS STRAIGHT SCKT - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## MS3459LS40-1S Specifications

Manufacturer Part Number MS3459LS40-1S   Manufacturer Amphenol Aerospace Operations   Category Connectors, Interconnects   Package -   Package -   Stries Military, MIL-DTL-5015   Connector Type Plug, Female Sockets   Number of Positions 30   Shell Size - Insert 40-1   Munting Type -   Mounting Type Free Hanging (In-Line)   Stening Type Threaded   Orientation N(Normal)   Ingress Protection Stailesstant   Shell Material, Finish Gold   Contact Finish Self Locking   Voltage - Rated Self Locking   Voltage - Rated -		
CategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Female SocketsNumber of Positions30Shell Size - Insert40-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionStainless SteelShell Material, FinishSelf LockingContact FinishSelf LockingVoltage - Rated-Current Rating13A, 23A	Manufacturer Part Number	MS3459LS40-1S
Circular ConnectorsPackage-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Female SocketsNumber of Positions30Shell Size - Insert40-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionStainless SteelShell Material, FinishSelf LockingFeaturesSelf LockingVoltage - Rated-Current Rating13A, 23A	Manufacturer	Amphenol Aerospace Operations
Package-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Female SocketsNumber of Positions30Shell Size - Insert40-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypePineadedOrientationNiormal)Ingress ProtectionFuid ResistantShell Material, FinishGoldContact FinishGoldVoltage - RatedSel LockingVoltage - RatedJa, 23A	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-5015Connector TypePlug, Female SocketsNumber of Positions30Shell Size - Insert40-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionFluid ResistantShell Material, FinishStainless SteelContact FinishSelf LockingVitage - Rated-Yurent Rating13A, 23A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions30Shell Size - Insert40-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionStainless SteelShell Material, FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating13A, 23A	Package	-
Number of Positions30Shell Size - Insert40-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionStainless SteelShell Material, FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating13A, 23A	Series	Military, MIL-DTL-5015
Shell Size - Insert40-1Shell Size, MIL-Mouning TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN(Normal)Ingress ProtectionFuid ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating13A, 23A	Connector Type	Plug, Female Sockets
Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN(Normal)Ingress ProtectionFluid ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating13A, 23A	Number of Positions	30
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedFortationN (Normal)OrientationFluid ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating13A, 23A	Shell Size - Insert	40-1
TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionFluid ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating13A, 23A	Shell Size, MIL	-
Fastening TypeThreadedOrientationN (Normal)Ingress ProtectionFluid ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating13A, 23A	Mounting Type	Free Hanging (In-Line)
OrientationN (Normal)Ingress ProtectionFluid ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating13A, 23A	Termination	Crimp
Ingress ProtectionFluid ResistantShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating13A, 23A	Fastening Type	Threaded
Shell Material, FinishStainless SteelContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating13A, 23A	Orientation	N (Normal)
Contact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating13A, 23A	Ingress Protection	Fluid Resistant
FeaturesSelf LockingVoltage - Rated-Current Rating13A, 23A	Shell Material, Finish	Stainless Steel
Voltage - Rated-Current Rating13A, 23A	Contact Finish	Gold
Current Rating 13A, 23A	Features	Self Locking
-	Voltage - Rated	-
Report errors?	Current Rating	13A, 23A
		Report errors?

#### MS3459LS40-1S Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### MS3459LS40-1S Payment Methods



### MS3459LS40-1S Shipping Methods



If you have any question about MS3459LS40-1S, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com