



MS3459W24-12PW Information

Heisener.com

Part Number MS3459W24-12PW

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 5POS STRAIGHT PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3459W24-12PW Specifications

| Manufacturer Part Number MS3459W24-12PW Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-5015 Connector Type Plug, Male Pins Number of Positions 5 Shell Size - Insert 24-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation W Ingress Protection Fluid Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Self Locking Voltage - Rated - Current Rating 23A, 80A | | |
|--|--------------------------|-------------------------------------|
| Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-5015 Connector Type Plug, Male Pins Number of Positions 5 Shell Size - Insert 24-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Threaded Orientation W Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Self Locking Voltage - Rated Current Rating 2- Connectors, Interconnects Circular Connectors Military, MIL-DTL-5015 Flug, Male Pins Free Hanging (In-Line) Crimp Threaded Corientation W Gold Features Self Locking Voltage - Rated - Current Rating 23A, 80A | Manufacturer Part Number | MS3459W24-12PW |
| Circular Connectors Package - Series Military, MIL-DTL-5015 Connector Type Plug, Male Pins Number of Positions 5 Shell Size - Insert 24-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation W Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Self Locking Voltage - Rated Current Rating 23A, 80A | Manufacturer | Amphenol Aerospace Operations |
| Package - Military, MIL-DTL-5015 Connector Type Plug, Male Pins Number of Positions 5 Shell Size - Insert 24-12 Shell Size, MIL - Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation W Ingress Protection Fluid Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Conact Finish Gold Features Self Locking Voltage - Rated Current Rating 23A, 80A | Category | Connectors, Interconnects |
| Series Military, MIL-DTL-5015 Connector Type Plug, Male Pins Number of Positions 5 Shell Size - Insert 24-12 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation W Ingress Protection Fluid Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Self Locking Voltage - Rated Current Rating 23A, 80A | | Circular Connectors |
| Connector Type Plug, Male Pins Number of Positions 5 Shell Size - Insert 24-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation W Ingress Protection Fluid Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Self Locking Voltage - Rated Current Rating 23A, 80A | Package | - |
| Number of Positions5Shell Size - Insert24-12Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationWIngress ProtectionFluid ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating23A, 80A | Series | Military, MIL-DTL-5015 |
| Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation W Ingress Protection Fluid Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Self Locking Voltage - Rated - Current Rating 24-12 August 19 August 19 Carpet 19 Carpe | Connector Type | Plug, Male Pins |
| Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Threaded Orientation W Ingress Protection Fluid Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Self Locking Voltage - Rated - Current Rating 23A, 80A | Number of Positions | 5 |
| Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationWIngress ProtectionFluid ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesSelf LockingVoltage - Rated-Current Rating23A, 80A | Shell Size - Insert | 24-12 |
| Termination Crimp Fastening Type Threaded Orientation W Ingress Protection Fluid Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Self Locking Voltage - Rated Current Rating 23A, 80A | Shell Size, MIL | - |
| Fastening Type Orientation W Ingress Protection Shell Material, Finish Contact Finish Gold Features Self Locking Voltage - Rated Current Rating Threaded Threaded W Contact Finish Aluminum, Olive Drab Cadmium Plated Gold Self Locking Voltage - Rated - Current Rating | Mounting Type | Free Hanging (In-Line) |
| Orientation W Ingress Protection Fluid Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Self Locking Voltage - Rated - Current Rating 23A, 80A | Termination | Crimp |
| Ingress Protection Shell Material, Finish Contact Finish Gold Features Self Locking Voltage - Rated Current Rating Fluid Resistant Aluminum, Olive Drab Cadmium Plated Gold Contact Finish Gold Self Locking 23A, 80A | Fastening Type | Threaded |
| Shell Material, Finish Contact Finish Gold Features Self Locking Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Gold Self Locking 23A, 80A | Orientation | W |
| Contact Finish Gold Features Self Locking Voltage - Rated - Current Rating 23A, 80A | Ingress Protection | Fluid Resistant |
| Features Self Locking Voltage - Rated - Current Rating 23A, 80A | Shell Material, Finish | Aluminum, Olive Drab Cadmium Plated |
| Voltage - Rated - Current Rating - 23A, 80A | Contact Finish | Gold |
| Current Rating 23A, 80A | Features | Self Locking |
| | Voltage - Rated | - |
| Report errors? | Current Rating | 23A, 80A |
| | | Report errors? |

MS3459W24-12PW Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3459W24-12PW Payment Methods



















MS3459W24-12PW Shipping Methods













If you have any question about MS3459W24-12PW, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com