



MS3470A14-4S Information

Heisener.com

Part Number MS3470A14-4S

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 4POS WALL MNT SCKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3470A14-4S Specifications

| Manufacturer Part Number MS3470A14-4S Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 14-4 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A | | |
|---|--------------------------|-----------------------------------|
| Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 14-4 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A | Manufacturer Part Number | MS3470A14-4S |
| Circular Connectors Package - Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 14-4 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A | Manufacturer | Amphenol Aerospace Operations |
| Package - Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 14-4 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A | Category | Connectors, Interconnects |
| Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 14-4 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features Voltage - Rated 600VAC Current Rating 23A | | Circular Connectors |
| Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 14-4 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A | Package | - |
| Number of Positions Shell Size - Insert 14-4 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Features Voltage - Rated Current Rating 23A | Series | Military, MIL-DTL-26482 Series II |
| Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Features Voltage - Rated Current Rating 23A | Connector Type | Receptacle, Female Sockets |
| Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features Voltage - Rated Current Rating 23A | Number of Positions | 4 |
| Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A | Shell Size - Insert | 14-4 |
| Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A | Shell Size, MIL | - |
| Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating Bayonet Lock Bayonet Lock Bayonet Lock Bayonet Lock N (Normal) Environment Resistant Aluminum, Anodized Black Plated 600VAC | Mounting Type | Panel Mount, Flange |
| Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A | Termination | Crimp |
| Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A | Fastening Type | Bayonet Lock |
| Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Anodized Black Plated Gold 23A | Orientation | N (Normal) |
| Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A | Ingress Protection | Environment Resistant |
| Features - Voltage - Rated 600VAC Current Rating 23A | Shell Material, Finish | Aluminum, Anodized Black Plated |
| Voltage - Rated 600VAC Current Rating 23A | Contact Finish | Gold |
| Current Rating 23A | Features | - |
| - | Voltage - Rated | 600VAC |
| Report errors? | Current Rating | 23A |
| | | Report errors? |

MS3470A14-4S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3470A14-4S Payment Methods



















MS3470A14-4S Shipping Methods













If you have any question about MS3470A14-4S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com