

MS3470A22-12S Information

Heisener.com

Part Number MS3470A22-12S

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 12POS WALL MNT SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3470A22-12S Specifications

Manufacturer Part Number MS3470A22-12S Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 12 Shell Size - Insert 22-12 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 12 Shell Size - Insert 22-12 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated Courrent Rating 2- Connectors, Interconnects Circular Connectors Hilitary, MIL-DTL-26482 Series II Connectors II Connector Shell Sockes II Connector Sockets	Manufacturer Part Number	MS3470A22-12S
Circular Connectors Package - Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 12 Shell Size - Insert 22-12 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 12 Shell Size - Insert 22-12 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A	Category	Connectors, Interconnects
Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 12 Shell Size - Insert 22-12 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features Voltage - Rated 600VAC Current Rating 23A		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 12 Shell Size - Insert 22-12 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A	Package	-
Number of Positions Shell Size - Insert 22-12 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features Voltage - Rated Current Rating 23A	Series	Military, MIL-DTL-26482 Series II
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Features Voltage - Rated Current Rating 22-12 24-12 25-12 26-	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features Voltage - Rated Current Rating 23A	Number of Positions	12
Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A	Shell Size - Insert	22-12
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating Bayonet Lock N (Normal) Environment Resistant Aluminum, Anodized Black Plated Gold - 23A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A	Termination	Crimp
Ingress Protection Environment Resistant Aluminum, Anodized Black Plated Contact Finish Gold Features Voltage - Rated Current Rating Environment Resistant Aluminum, Anodized Black Plated Gold 23A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Anodized Black Plated Gold Contact Finish Gold - 23A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC Current Rating 23A	Shell Material, Finish	Aluminum, Anodized Black Plated
Voltage - Rated 600VAC Current Rating 23A	Contact Finish	Gold
Current Rating 23A	Features	-
	Voltage - Rated	600VAC
Report errors?	Current Rating	23A
		Report errors?

MS3470A22-12S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3470A22-12S Payment Methods



















MS3470A22-12S Shipping Methods













If you have any question about MS3470A22-12S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com