



## MS3470A8-98P Information

Heisener.com

Part Number MS3470A8-98P

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 3POS WALL MNT PINS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **MS3470A8-98P Specifications**

Manufacturer Part NumberMS3470A8-98PManufacturerAmphenol Aerospace OperationsCategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-26482 Series IIConnector TypeReceptacle, Male PinsNumber of Positions3Shell Size - Insert8-98Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodized Black PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A		
Category Connectors, Interconnects Circular Connectors  Package - Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Male Pins Number of Positions 3 Shell Size - Insert 8-98 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated Current Rating  Circular Connectors Military, MIL-DTL-26482 Series II Receptacle, Male Pins  8-98 8-98 8-98 8-98 Panel Mount, Flange Crimp Panel Mount, Flange Crimp Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated CovAC Current Rating	Manufacturer Part Number	MS3470A8-98P
Circular Connectors  Package - Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Male Pins Number of Positions 3 Shell Size - Insert 8-98 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated Convert Rating 7-5A	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-26482 Series II  Connector Type Receptacle, Male Pins  Number of Positions 3  Shell Size - Insert 8-98  Shell Size, MIL - Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Anodized Black Plated  Contact Finish Gold  Features - Voltage - Rated 600VAC  Current Rating 7.5A	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-26482 Series IIConnector TypeReceptacle, Male PinsNumber of Positions3Shell Size - Insert8-98Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodized Black PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions3Shell Size - Insert8-98Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodized Black PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Package	-
Number of Positions3Shell Size - Insert8-98Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodized Black PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Series	Military, MIL-DTL-26482 Series II
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated  Contact Finish Features - Voltage - Rated 600VAC Current Rating 7.5A	Number of Positions	3
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodized Black PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Shell Size - Insert	8-98
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  Voltage - Rated  Current Rating  Aluminum, Anodized Black Plated  Gold  600VAC  7.5A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Material, Finish	Aluminum, Anodized Black Plated
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	-
-	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

#### MS3470A8-98P Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MS3470A8-98P Payment Methods





















## MS3470A8-98P Shipping Methods













If you have any question about MS3470A8-98P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com