



MS3470L20-39SW Information

Heisener.com

Part Number MS3470L20-39SW

Manufacturer TE Connectivity Deutsch Connectors

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 39POS FLANGE W/SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3470L20-39SW Specifications

| Manufacturer Part Number MS3470L20-39SW Manufacturer TE Connectivity Deutsch Connectors Category Connectors, Interconnects Package - Series Military, MIL-DTL-26482 G Series II, AFD Connector Type Receptacle, Female Sockets Number of Positions 39 Shell Size - Insert 20-39 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated - Current Rating 7.5A, 13A | | |
|---|--------------------------|--|
| Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-26482 G Series II, AFD Connector Type Receptacle, Female Sockets Number of Positions 39 Shell Size - Insert 20-39 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated Current Rating Tyes Cinnectors Circular Connectors Circular Connectors Military, MIL-DTL-26482 G Series II, AFD Alumitary, MIL-DTL-26482 G Series II, AFD Consector Series II, AFD Alumitary, MIL-DTL-26482 G Series II, | Manufacturer Part Number | MS3470L20-39SW |
| Circular ConnectorsPackage-SeriesMilitary, MIL-DTL-26482 G Series II, AFDConnector TypeReceptacle, Female SocketsNumber of Positions39Shell Size - Insert20-39Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A, 13A | Manufacturer | TE Connectivity Deutsch Connectors |
| Package-SeriesMilitary, MIL-DTL-26482 G Series II, AFDConnector TypeReceptacle, Female SocketsNumber of Positions39Shell Size - Insert20-39Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A, 13A | Category | Connectors, Interconnects |
| SeriesMilitary, MIL-DTL-26482 G Series II, AFDConnector TypeReceptacle, Female SocketsNumber of Positions39Shell Size - Insert20-39Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A, 13A | | Circular Connectors |
| Connector TypeReceptacle, Female SocketsNumber of Positions39Shell Size - Insert20-39Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A, 13A | Package | - |
| Number of Positions39Shell Size - Insert20-39Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A, 13A | Series | Military, MIL-DTL-26482 G Series II, AFD |
| Shell Size - Insert20-39Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A, 13A | Connector Type | Receptacle, Female Sockets |
| Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features - Voltage - Rated - Current Rating 7.5A, 13A | Number of Positions | 39 |
| Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A, 13A | Shell Size - Insert | 20-39 |
| Termination Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated - Current Rating 7.5A, 13A | Shell Size, MIL | - |
| Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated - Current Rating 7,5A, 13A | Mounting Type | Panel Mount, Flange |
| Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated - Current Rating 7.5A, 13A | Termination | Crimp |
| Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated - Current Rating 7.5A, 13A | Fastening Type | Bayonet Lock |
| Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating 7.5A, 13A | Orientation | W |
| Contact Finish Gold Features - Voltage - Rated - Current Rating 7.5A, 13A | Ingress Protection | Environment Resistant |
| Features - Voltage - Rated - Current Rating 7.5A, 13A | Shell Material, Finish | Aluminum, Nickel Plated, Electroless |
| Voltage - Rated - Current Rating 7.5A, 13A | Contact Finish | Gold |
| Current Rating 7.5A, 13A | Features | - |
| | Voltage - Rated | - |
| Domont owners | Current Rating | 7.5A, 13A |
| Report errors? | | Report errors? |

MS3470L20-39SW Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3470L20-39SW Payment Methods


































If you have any question about MS3470L20-39SW, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com