



MS3471A18-8S Information

Heisener.com

Part Number MS3471A18-8S

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 8POS STRAIGHT SCKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3471A18-8S Specifications

Manufacturer Part Number MS3471A18-8S Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 8 Shell Size - Insert 18-8 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 8 Shell Size - Insert 18-8 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated Courrent Rating 23A	Manufacturer Part Number	MS3471A18-8S
Circular Connectors Package - Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 8 Shell Size - Insert 18-8 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 8 Shell Size - Insert 18-8 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A	Category	Connectors, Interconnects
Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 8 Shell Size - Insert 18-8 Shell Size, MIL		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 8 Shell Size - Insert 18-8 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A	Package	-
Number of Positions Shell Size - Insert 18-8 Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Features Voltage - Rated Current Rating 8 8 8 18-8 8 18-8 18-8 18-8 Free Hanging (In-Line) Crimp Bayonet Lock N (Normal) Environment Resistant Aluminum, Anodized Black Plated Gold Features - Voltage - Rated 600VAC Current Rating	Series	Military, MIL-DTL-26482 Series II
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Features Voltage - Rated Current Rating 18-8 Environment Free Hanging (In-Line) Crimp Bayonet Lock N (Normal) Environment Resistant Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC 23A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated Current Rating 23A	Number of Positions	8
Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A	Shell Size - Insert	18-8
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating Bayonet Lock N (Normal) Environment Resistant Aluminum, Anodized Black Plated Gold - 23A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A	Termination	Crimp
Ingress Protection Environment Resistant Aluminum, Anodized Black Plated Contact Finish Gold Features Voltage - Rated Current Rating Environment Resistant Aluminum, Anodized Black Plated Gold 23A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Anodized Black Plated Gold 23A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC Current Rating 23A	Shell Material, Finish	Aluminum, Anodized Black Plated
Voltage - Rated 600VAC Current Rating 23A	Contact Finish	Gold
Current Rating 23A	Features	-
-	Voltage - Rated	600VAC
Report errors?	Current Rating	23A
		Report errors?

MS3471A18-8S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3471A18-8S Payment Methods



















MS3471A18-8S Shipping Methods













If you have any question about MS3471A18-8S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com