



### MS3471L12-8P Information

Heisener.com

Part Number MS3471L12-8P

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 8POS INLINE PIN

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **MS3471L12-8P Specifications**

Manufacturer Part NumberMS3471L12-8PManufacturerAmphenol Aerospace OperationsCategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-26482 Series IIConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A		
Category Connectors, Interconnects Circular Connectors  Package - Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Male Pins Number of Positions 8 Shell Size - Insert 12-8 Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated  Connectors, Interconnects Circular Connectors  Hall Connectors Interconnects  Connectors Interconnects Connectors Interconnects Connectors Interconnectors Interconnectors II Connector II	Manufacturer Part Number	MS3471L12-8P
Circular Connectors  Package - Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Male Pins Number of Positions 8 Shell Size - Insert 12-8 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated  Military, MIL-OTL-26482 Series II  Ricular Connectors II  Military, MIL-DTL-26482 Series II  Receptacle, Male Pins  8 Nilitary, MIL-DTL-26482 Series II  Receptacle, Male Pins  Nell Male Pins  Aluminum, Vickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-26482 Series II  Connector Type Receptacle, Male Pins  Number of Positions 8  Shell Size - Insert 12-8  Shell Size, MIL Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Gold  Features - GOVAC	Category	Connectors, Interconnects
Series Military, MIL-DTL-26482 Series II  Connector Type Receptacle, Male Pins  Number of Positions 8  Shell Size - Insert 12-8  Shell Size, MIL		Circular Connectors
Connector Type Receptacle, Male Pins Number of Positions 8 Shell Size - Insert 12-8 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated 600VAC	Package	-
Number of Positions  Shell Size - Insert  12-8  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Crimp  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum, Nickel Plated, Electroless  Contact Finish  Gold  Features  Voltage - Rated  8  8  8  8  8  12-8  Free Hanging (In-Line)  Crimp  Bayonet Lock  N (Normal)  Environment Resistant  Aluminum, Nickel Plated, Electroless  Gold	Series	Military, MIL-DTL-26482 Series II
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum, Nickel Plated, Electroless  Contact Finish  Gold  Features  Voltage - Rated  12-8  Ingress Protection  Grimp  Free Hanging (In-Line)  Grimp  Gold  Fouring  Fouring  Gold  Fouring  Gold  Fouring  Gold  Fouring  Gold  Fouring  Gold  Fouring  Gold  Fouring  Free Hanging (In-Line)  F	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold  Features - Voltage - Rated  600VAC	Number of Positions	8
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VAC	Shell Size - Insert	12-8
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Nickel Plated, Electroless  Contact Finish  Gold  Features  -  Voltage - Rated  Bayonet Lock  Bayonet Lock  Bayonet Lock  Resistant  600VAC	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  -  Voltage - Rated  Aluminum, Nickel Plated, Electroless  Gold  600VAC	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated 600VAC	Contact Finish	Gold
-	Features	-
Current Rating 7.5A	Voltage - Rated	600VAC
	Current Rating	7.5A
Report errors?		Report errors?

### MS3471L12-8P Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MS3471L12-8P Payment Methods





















### MS3471L12-8P Shipping Methods













If you have any question about MS3471L12-8P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com