



### MS3472L14-4S Information

Heisener.com

Part Number MS3472L14-4S

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 4POS WALL MNT SCKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **MS3472L14-4S Specifications**

Manufacturer Part Number       MS3472L14-4S         Manufacturer       Amphenol Aerospace Operations         Category       Connectors, Interconnects         Package       -         Series       Military, MIL-DTL-26482 Series II         Connector Type       Receptacle, Female Sockets         Number of Positions       4         Shell Size - Insert       14-4         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Nickel Plated, Electroless         Contact Finish       Gold         Features       -         Voltage - Rated       600VAC         Current Rating       23A		
Category Connectors, Interconnects Circular Connectors  Package - Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating  23A	Manufacturer Part Number	MS3472L14-4S
Circular Connectors  Package Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 14-4 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating  23A	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 14-4 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A	Category	Connectors, Interconnects
Series Military, MIL-DTL-26482 Series II  Connector Type Receptacle, Female Sockets  Number of Positions 4  Shell Size - Insert 14-4  Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Nickel Plated, Electroless  Contact Finish Gold  Features  Voltage - Rated 600VAC  Current Rating 23A		Circular Connectors
Connector Type Receptacle, Female Sockets  Number of Positions 4  Shell Size - Insert 14-4  Shell Size, MIL -  Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Nickel Plated, Electroless  Contact Finish Gold  Features -  Voltage - Rated 600VAC  Current Rating 23A	Package	-
Number of Positions  Shell Size - Insert  14-4  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum, Nickel Plated, Electroless  Contact Finish  Features  Voltage - Rated  Current Rating  23A	Series	Military, MIL-DTL-26482 Series II
Shell Size - Insert  Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features Voltage - Rated Current Rating  14-4	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated Current Rating 23A	Number of Positions	4
Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold  Features - Voltage - Rated 600VAC Current Rating 23A	Shell Size - Insert	14-4
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 23A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Nickel Plated, Electroless Gold 23A	Orientation	N (Normal)
Contact Finish Gold  Features -  Voltage - Rated 600VAC  Current Rating 23A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC Current Rating 23A	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated 600VAC Current Rating 23A	Contact Finish	Gold
Current Rating 23A	Features	-
-	Voltage - Rated	600VAC
Report errors?	Current Rating	23A
		Report errors?

#### MS3472L14-4S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# MS3472L14-4S Payment Methods



















## MS3472L14-4S Shipping Methods













If you have any question about MS3472L14-4S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com