



### MS3472L16-23SW Information

Heisener.com

Part Number MS3472L16-23SW

Manufacturer TE Connectivity Deutsch Connectors

**Category** Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 23POS FLANGE W/SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## MS3472L16-23SW Specifications

| Manufacturer Part Number     MS3472L16-23SW       Manufacturer     TE Connectivity Deutsch Connectors       Category     Connectors, Interconnects       Package     -       Series     Military, MIL-DTL-26482 G Series II, AFD       Connector Type     Receptacle, Female Sockets       Number of Positions     23       Shell Size - Insert     16-23       Shell Size, MIL     -       Mounting Type     Panel Mount, Flange       Termination     Crimp       Fastening Type     Bayonet Lock       Orientation     W       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum, Nickel Plated, Electroless       Contact Finish     Gold       Features     -       Voltage - Rated     -       Current Rating     7.5A, 13A |                          |  |
|--|--------------------------|--|
| CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-26482 G Series II, AFDConnector TypeReceptacle, Female SocketsNumber of Positions23Shell Size - Insert16-23Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A, 13A  | Manufacturer Part Number | MS3472L16-23SW                           |
| Circular Connectors  Package - Series Military, MIL-DTL-26482 G Series II, AFD  Connector Type Receptacle, Female Sockets  Number of Positions 23 Shell Size - Insert 16-23 Shell Size, MIL - Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock Orientation W  Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated Current Rating 7.5A, 13A  | Manufacturer             | TE Connectivity Deutsch Connectors       |
| Package-SeriesMilitary, MIL-DTL-26482 G Series II, AFDConnector TypeReceptacle, Female SocketsNumber of Positions23Shell Size - Insert16-23Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A, 13A   | Category                 | Connectors, Interconnects                |
| SeriesMilitary, MIL-DTL-26482 G Series II, AFDConnector TypeReceptacle, Female SocketsNumber of Positions23Shell Size - Insert16-23Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A, 13A   |                          | Circular Connectors                      |
| Connector TypeReceptacle, Female SocketsNumber of Positions23Shell Size - Insert16-23Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A, 13A   | Package                  | -  |
| Number of Positions23Shell Size - Insert16-23Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A, 13A   | Series                   | Military, MIL-DTL-26482 G Series II, AFD |
| Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated Current Rating 7.5A, 13A   | Connector Type           | Receptacle, Female Sockets               |
| Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features - Voltage - Rated - Current Rating 7.5A, 13A  | Number of Positions      | 23                                       |
| Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A, 13A  | Shell Size - Insert      | 16-23                                    |
| Termination Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated - Current Rating 7.5A, 13A   | Shell Size, MIL          | -  |
| Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated - Current Rating 7,5A, 13A   | Mounting Type            | Panel Mount, Flange                      |
| Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated - Current Rating 7.5A, 13A   | Termination              | Crimp                                    |
| Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated - Current Rating 7.5A, 13A   | Fastening Type           | Bayonet Lock                             |
| Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating 7.5A, 13A   | Orientation              | W  |
| Contact Finish Gold Features - Voltage - Rated - Current Rating 7.5A, 13A  | Ingress Protection       | Environment Resistant                    |
| Features - Voltage - Rated - Current Rating 7.5A, 13A  | Shell Material, Finish   | Aluminum, Nickel Plated, Electroless     |
| Voltage - Rated - Current Rating 7.5A, 13A   | Contact Finish           | Gold                                     |
| Current Rating 7.5A, 13A   | Features                 | -  |
|  | Voltage - Rated          | -  |
| Report errors?   | Current Rating           | 7.5A, 13A                                |
|  |                          | Report errors?                           |

## MS3472L16-23SW Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MS3472L16-23SW Payment Methods

































If you have any question about MS3472L16-23SW, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com