



MS3472L20-39SX Information

Heisener.com

Part Number MS3472L20-39SX

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 39POS FLANGE W/SKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3472L20-39SX Specifications

Manufacturer Part Number MS3472L20-39SX Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 39 Shell Size - Insert 20-39 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation X Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 39 Shell Size - Insert 20-39 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation X Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated Current Rating Tone	Manufacturer Part Number	MS3472L20-39SX
Package-SeriesMilitary, MIL-DTL-26482 Series IIConnector TypeReceptacle, Female SocketsNumber of Positions39Shell Size - Insert20-39Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A, 13A	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 39 Shell Size - Insert 20-39 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation X Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7,5A, 13A	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-26482 Series IIConnector TypeReceptacle, Female SocketsNumber of Positions39Shell Size - Insert20-39Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A, 13A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions39Shell Size - Insert20-39Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A, 13A	Package	-
Number of Positions39Shell Size - Insert20-39Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A, 13A	Series	Military, MIL-DTL-26482 Series II
Shell Size - Insert20-39Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A, 13A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation X Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Number of Positions	39
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A, 13A	Shell Size - Insert	20-39
Termination Crimp Fastening Type Bayonet Lock Orientation X Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Shell Size, MIL	-
Fastening Type Orientation X Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating Bayonet Lock X Auminum, Nickel Plated, Electroless Gold 7.5A, 13A	Mounting Type	Panel Mount, Flange
Orientation X Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Nickel Plated, Electroless Gold	Orientation	X
Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated 600VAC Current Rating 7.5A, 13A	Contact Finish	Gold
Current Rating 7.5A, 13A	Features	-
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A, 13A
The post of the second		Report errors?

MS3472L20-39SX Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3472L20-39SX Payment Methods





















MS3472L20-39SX Shipping Methods













If you have any question about MS3472L20-39SX, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com