



MS3474L14-9SY Information

Heisener.com

Part Number MS3474L14-9SY

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 9POS JAM NUT SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3474L14-9SY Specifications

| Manufacturer Part Number MS3474L14-9SY Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 9 Shell Size - Insert 14-9 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation Y Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 23A | | |
|---|--------------------------|--|
| Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 9 Shell Size - Insert 14-9 Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation Y Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated Current Rating 7, 5, 23A | Manufacturer Part Number | MS3474L14-9SY |
| Package-SeriesMilitary, MIL-DTL-26482 Series IIConnector TypeReceptacle, Female SocketsNumber of Positions9Shell Size - Insert14-9Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A, 23A | Manufacturer | Amphenol Aerospace Operations |
| Package - Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 9 Shell Size - Insert 14-9 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation Y Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 23A | Category | Connectors, Interconnects |
| Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Female Sockets Number of Positions 9 Shell Size - Insert 14-9 Shell Size, MIL | | Circular Connectors |
| Connector TypeReceptacle, Female SocketsNumber of Positions9Shell Size - Insert14-9Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A, 23A | Package | - |
| Number of Positions9Shell Size - Insert14-9Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A, 23A | Series | Military, MIL-DTL-26482 Series II |
| Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation Y Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 23A | Connector Type | Receptacle, Female Sockets |
| Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Crimp Fastening Type Bayonet Lock Orientation Y Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features - Voltage - Rated 600VAC Current Rating 7 Panel Mount, Bulkhead - Front Side Nut Environment Side Nut Aut Orientation Y Environment Resistant Aluminum, Nickel Plated, Electroless Gold - Voltage - Rated 7.5A, 23A | Number of Positions | 9 |
| Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A, 23A | Shell Size - Insert | 14-9 |
| Termination Crimp Fastening Type Bayonet Lock Orientation Y Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7,5A, 23A | Shell Size, MIL | - |
| Fastening Type Orientation Y Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 23A | Mounting Type | Panel Mount, Bulkhead - Front Side Nut |
| Orientation Y Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 23A | Termination | Crimp |
| Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 23A | Fastening Type | Bayonet Lock |
| Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Nickel Plated, Electroless Gold - 7.5A, 23A | Orientation | Y |
| Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 23A | Ingress Protection | Environment Resistant |
| Features - Voltage - Rated 600VAC Current Rating 7.5A, 23A | Shell Material, Finish | Aluminum, Nickel Plated, Electroless |
| Voltage - Rated 600VAC Current Rating 7.5A, 23A | Contact Finish | Gold |
| Current Rating 7.5A, 23A | Features | - |
| | Voltage - Rated | 600VAC |
| | Current Rating | 7.5A, 23A |
| Report errors? | | Report errors? |

MS3474L14-9SY Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3474L14-9SY Payment Methods



















MS3474L14-9SY Shipping Methods













If you have any question about MS3474L14-9SY, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com