



## MS3474W14-19P Information

Heisener.com

Part Number MS3474W14-19P

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 19POS JAM NUT W/PINS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# MS3474W14-19P Specifications

Manufacturer Part Number       MS3474W14-19P         Manufacturer       Amphenol Aerospace Operations         Category       Connectors, Interconnects         Package       -         Series       Military, MIL-DTL-26482 Series II         Connector Type       Receptacle, Male Pins         Number of Positions       19         Shell Size - Insert       14-19         Shell Size, MIL       -         Mounting Type       Panel Mount, Bulkhead - Front Side Nut         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Olive Drab Cadmium Plated         Contact Finish       Gold         Features       -         Voltage - Rated       600VAC         Current Rating       7.5A		
Category Connectors, Interconnects Circular Connectors  Package - Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Male Pins Number of Positions 19 Shell Size - Insert 14-19 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated Current Rating 7,5A	Manufacturer Part Number	MS3474W14-19P
Package-SeriesMilitary, MIL-DTL-26482 Series IIConnector TypeReceptacle, Male PinsNumber of Positions19Shell Size - Insert14-19Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Manufacturer	Amphenol Aerospace Operations
Package - Series Military, MIL-DTL-26482 Series II Connector Type Receptacle, Male Pins Number of Positions 19 Shell Size - Insert 14-19 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 17.5A	Category	Connectors, Interconnects
Series Military, MIL-DTL-26482 Series II  Connector Type Receptacle, Male Pins  Number of Positions 19  Shell Size - Insert 14-19  Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions19Shell Size - Insert14-19Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Package	-
Number of Positions19Shell Size - Insert14-19Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Series	Military, MIL-DTL-26482 Series II
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Bulkhead - Front Side Nut  Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 600VAC Current Rating 7.5A	Number of Positions	19
Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Shell Size - Insert	14-19
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  - Voltage - Rated  Current Rating  Aluminum, Olive Drab Cadmium Plated  Gold  600VAC  7.5A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	-
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

#### MS3474W14-19P Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# MS3474W14-19P Payment Methods



















### MS3474W14-19P Shipping Methods













If you have any question about MS3474W14-19P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com