



MS3475A14-19P Information

Heisener.com

Part Number MS3475A14-19P

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 19POS STRAIGHT PINS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3475A14-19P Specifications

Manufacturer Part Number MS3475A14-19P Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-26482 Series II Connector Type Plug, Male Pins Number of Positions 19 Shell Size - Insert 14-19 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC Current Rating 7.5A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-26482 Series II Connector Type Plug, Male Pins Number of Positions 19 Shell Size - Insert 14-19 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features Voltage - Rated Convert Rating 7,5A	Manufacturer Part Number	MS3475A14-19P
Circular Connectors Package - Series Military, MIL-DTL-26482 Series II Connector Type Plug, Male Pins Number of Positions 19 Shell Size - Insert 14-19 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features Shielded Voltage - Rated Courrent Rating 7,5A	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-26482 Series II Connector Type Plug, Male Pins Number of Positions 19 Shell Size - Insert 14-19 Shell Size, MIL - Crimp Fastening Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC Current Rating 7.5A	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-26482 Series IIConnector TypePlug, Male PinsNumber of Positions19Shell Size - Insert14-19Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodized Black PlatedContact FinishGoldFeaturesShieldedVoltage - Rated600VACCurrent Rating7.5A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions19Shell Size - Insert14-19Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodized Black PlatedContact FinishGoldFeaturesShieldedVoltage - Rated600VACCurrent Rating7.5A	Package	-
Number of Positions19Shell Size - Insert14-19Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodized Black PlatedContact FinishGoldFeaturesShieldedVoltage - Rated600VACCurrent Rating7.5A	Series	Military, MIL-DTL-26482 Series II
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Features Shielded Voltage - Rated Current Rating 7.5A	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Features Shielded Voltage - Rated 600VAC Current Rating 7	Number of Positions	19
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodized Black PlatedContact FinishGoldFeaturesShieldedVoltage - Rated600VACCurrent Rating7.5A	Shell Size - Insert	14-19
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC Current Rating 7.5A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC Current Rating 7.5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating Aluminum, Anodized Black Plated Gold Gold Shielded 7.5A	Orientation	N (Normal)
Contact Finish Gold Features Shielded Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated 600VAC Current Rating 7.5A	Shell Material, Finish	Aluminum, Anodized Black Plated
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	Shielded
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

MS3475A14-19P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3475A14-19P Payment Methods



















MS3475A14-19P Shipping Methods













If you have any question about MS3475A14-19P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com