



MS3475L16-26SZ Information

Heisener.com

Part Number MS3475L16-26SZ

Manufacturer TE Connectivity Deutsch Connectors

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 26POS INLINE SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3475L16-26SZ Specifications

Manufacturer Part Number Manufacturer TE Connectivity Deutsch Connectors Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-26482 G Series II, AFD Connector Type Plug, Female Sockets Number of Positions 26 Shell Size - Insert 16-26 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation Z Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated - Current Rating 7.5A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-26482 G Series II, AFD Connector Type Plug, Female Sockets Number of Positions 26 Shell Size - Insert 16-26 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Manufacturer Part Number	MS3475L16-26SZ
Circular Connectors Package - Series Military, MIL-DTL-26482 G Series II, AFD Connector Type Plug, Female Sockets Number of Positions 26 Shell Size - Insert 16-26 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation Z Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Manufacturer	TE Connectivity Deutsch Connectors
Package-SeriesMilitary, MIL-DTL-26482 G Series II, AFDConnector TypePlug, Female SocketsNumber of Positions26Shell Size - Insert16-26Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationZIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Category	Connectors, Interconnects
Series Military, MIL-DTL-26482 G Series II, AFD Connector Type Plug, Female Sockets Number of Positions 26 Shell Size - Insert 16-26 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions26Shell Size - Insert16-26Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationZIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Package	-
Number of Positions26Shell Size - Insert16-26Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationZIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Series	Military, MIL-DTL-26482 G Series II, AFD
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features Shielded Voltage - Rated Current Rating 16-26 Free Hanging (In-Line) Free Hanging (In-Line) Crimp Bayonet Lock Aluminum, Vickel Bayonet Lock Coltact Shielded Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Number of Positions	26
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationZIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A	Shell Size - Insert	16-26
Termination Crimp Fastening Type Bayonet Lock Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Mounting Type	Free Hanging (In-Line)
Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating Aluminum, Nickel Plated, Electroless Gold Told Shielded - Told T	Orientation	Z
Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated - Current Rating 7.5A	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated - Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	Shielded
	Voltage - Rated	-
Report errors?	Current Rating	7.5A
		Report errors?

MS3475L16-26SZ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3475L16-26SZ Payment Methods



















MS3475L16-26SZ Shipping Methods













If you have any question about MS3475L16-26SZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com