



### MS3475L24-19PY Information

Heisener.com

Part Number MS3475L24-19PY

Manufacturer TE Connectivity Deutsch Connectors

**Category** Connectors, Interconnects

Circular Connectors

**Description** CONN PLUG 19POS INLINE PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **MS3475L24-19PY Specifications**

Manufacturer Part Number     MS3475L24-19PY       Manufacturer     TE Connectivity Deutsch Connectors       Category     Connectors, Interconnects       Package     -       Series     Military, MIL-DTL-26482 G Series II, AFD       Connector Type     Plug, Male Pins       Number of Positions     19       Shell Size - Insert     24-19       Shell Size, MIL     -       Mounting Type     Free Hanging (In-Line)       Termination     Crimp       Fastening Type     Bayonet Lock       Orientation     Y       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum, Nickel Plated, Electroless       Contact Finish     Gold       Features     Shielded       Voltage - Rated     -       Current Rating     23A		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-26482 G Series II, AFDConnector TypePlug, Male PinsNumber of Positions19Shell Size - Insert24-19Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating23A	Manufacturer Part Number	MS3475L24-19PY
Package-SeriesMilitary, MIL-DTL-26482 G Series II, AFDConnector TypePlug, Male PinsNumber of Positions19Shell Size - Insert24-19Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating23A	Manufacturer	TE Connectivity Deutsch Connectors
Package-SeriesMilitary, MIL-DTL-26482 G Series II, AFDConnector TypePlug, Male PinsNumber of Positions19Shell Size - Insert24-19Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating23A	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-26482 G Series II, AFDConnector TypePlug, Male PinsNumber of Positions19Shell Size - Insert24-19Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating23A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions19Shell Size - Insert24-19Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating23A	Package	-
Number of Positions19Shell Size - Insert24-19Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating23A	Series	Military, MIL-DTL-26482 G Series II, AFD
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Bayonet Lock Orientation Y Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features Shielded Voltage - Rated Current Rating 24-19 Erves Erves 24-19 Erve Hanging (In-Line) Free Hanging (In-Line) Erve Hanging (In-Line)  Crimp Factores Bayonet Lock Orimp Factores Shoulded  Voltage - Rated - 23A	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Bayonet Lock Orientation Y Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features Shielded  Voltage - Rated Current Rating 23A	Number of Positions	19
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating23A	Shell Size - Insert	24-19
Termination Crimp Fastening Type Bayonet Lock Orientation Y Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated Current Rating 23A	Shell Size, MIL	-
Fastening Type  Orientation  Y  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Nickel Plated, Electroless  Contact Finish  Gold  Features  Shielded  Voltage - Rated  -  Current Rating  Bayonet Lock  Y  Auminum, Nickel Plated, Electroless  Gold  Shielded	Mounting Type	Free Hanging (In-Line)
Orientation Y Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 23A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 23A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating 23A	Orientation	Y
Contact Finish Gold Features Shielded  Voltage - Rated - Current Rating 23A	Ingress Protection	Environment Resistant
Features Shielded  Voltage - Rated - Current Rating 23A	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated - Current Rating 23A	Contact Finish	Gold
Current Rating 23A	Features	Shielded
	Voltage - Rated	-
Report errors?	Current Rating	23A
		Report errors?

#### MS3475L24-19PY Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MS3475L24-19PY Payment Methods



















# MS3475L24-19PY Shipping Methods













If you have any question about MS3475L24-19PY, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com