



MS3475W20-39SZ Information

Heisener.com

Part Number MS3475W20-39SZ

Manufacturer TE Connectivity Deutsch Connectors

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 39POS INLINE SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3475W20-39SZ Specifications

Manufacturer Part Number MS3475W20-39SZ Manufacturer TE Connectivity Deutsch Connectors Category Connectors, Interconnects Package - Series Military, MIL-DTL-26482 G Series II, AFD Connector Type Plug, Female Sockets Number of Positions 39 Shell Size - Insert 20-39 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-26482 G Series II, AFD Connector Type Plug, Female Sockets Number of Positions 39 Shell Size - Insert 20-39 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation Z Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Voltage - Rated Voltage - Rated Current Rating 7 - 5.5, 13A	Manufacturer Part Number	MS3475W20-39SZ
Package-SeriesMilitary, MIL-DTL-26482 G Series II, AFDConnector TypePlug, Female SocketsNumber of Positions39Shell Size - Insert20-39Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationZIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A	Manufacturer	TE Connectivity Deutsch Connectors
Package-SeriesMilitary, MIL-DTL-26482 G Series II, AFDConnector TypePlug, Female SocketsNumber of Positions39Shell Size - Insert20-39Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationZIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-26482 G Series II, AFDConnector TypePlug, Female SocketsNumber of Positions39Shell Size - Insert20-39Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationZIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions39Shell Size - Insert20-39Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationZIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A	Package	-
Number of Positions39Shell Size - Insert20-39Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationZIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A	Series	Military, MIL-DTL-26482 G Series II, AFD
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Shielded Voltage - Rated Current Rating 7.5A, 13A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Shielded Voltage - Rated Current Rating 7.5A, 13A	Number of Positions	39
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationZIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A	Shell Size - Insert	20-39
Termination Crimp Fastening Type Bayonet Lock Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A, 13A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Mounting Type	Free Hanging (In-Line)
Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A, 13A	Orientation	Z
Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated - Current Rating 7.5A, 13A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated - Current Rating 7.5A, 13A	Contact Finish	Gold
Current Rating 7.5A, 13A	Features	Shielded
	Voltage - Rated	-
Report errors?	Current Rating	7.5A, 13A
		Report errors?

MS3475W20-39SZ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3475W20-39SZ Payment Methods



















MS3475W20-39SZ Shipping Methods













If you have any question about MS3475W20-39SZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com