

MS3476A24-19S Information

Heisener.com

Part Number MS3476A24-19S

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 19POS INLINE SCKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3476A24-19S Specifications

Manufacturer Part Number MS3476A24-19S Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-26482 Series II Connector Type Plug, Female Sockets Number of Positions 19 Shell Size - Insert 24-19 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 1000VAC Current Rating 23A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-26482 Series II Connector Type Plug, Female Sockets Number of Positions 19 Shell Size - Insert 24-19 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated Lock Urrent Rating 23A	Manufacturer Part Number	MS3476A24-19S
Circular Connectors Package - Series Military, MIL-DTL-26482 Series II Connector Type Plug, Female Sockets Number of Positions 19 Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated Lower Military, MIL-DTL-26482 Series II Military, MIL-DTL-26482 Series II Military, MIL-DTL-26482 Series II Military, MIL-DTL-26482 Series II Flatters 19 Shell Sockets IV Voltage - Rated 1000VAC Current Rating 23A	Manufacturer	Amphenol Aerospace Operations
Package-SeriesMilitary, MIL-DTL-26482 Series IIConnector TypePlug, Female SocketsNumber of Positions19Shell Size - Insert24-19Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodized Black PlatedContact FinishGoldFeatures-Voltage - Rated1000VACCurrent Rating23A	Category	Connectors, Interconnects
Series Military, MIL-DTL-26482 Series II Connector Type Plug, Female Sockets Number of Positions 19 Shell Size - Insert 24-19 Shell Size, MIL		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions19Shell Size - Insert24-19Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodized Black PlatedContact FinishGoldFeatures-Voltage - Rated1000VACCurrent Rating23A	Package	-
Number of Positions19Shell Size - Insert24-19Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodized Black PlatedContact FinishGoldFeatures-Voltage - Rated1000VACCurrent Rating23A	Series	Military, MIL-DTL-26482 Series II
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Features - Voltage - Rated 1000VAC Current Rating 24-19 24-19 24-19 24-19 24-19 24-19 24-19 Free Hanging (In-Line) Free Hanging (In-Line) Crimp Bayonet Lock N (Normal) Environment Resistant Aluminum, Anodized Black Plated Contact Finish Gold 23A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Features - Voltage - Rated 1000VAC Current Rating - Contact Finish 23A	Number of Positions	19
Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 1000VAC Current Rating 23A	Shell Size - Insert	24-19
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 1000VAC Current Rating 23A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 1000VAC Current Rating Bayonet Lock N (Normal) Environment Resistant Aluminum, Anodized Black Plated Cold Gold - 23A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodized Black Plated Contact Finish Gold Features - Voltage - Rated 1000VAC Current Rating 23A	Termination	Crimp
Ingress Protection Environment Resistant Aluminum, Anodized Black Plated Contact Finish Gold Features Voltage - Rated Current Rating Environment Resistant Aluminum, Anodized Black Plated Gold 23A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Anodized Black Plated Gold Contact Finish Gold Cold Cold Cold Cold Cold Cold Cold C	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 1000VAC Current Rating 23A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 1000VAC Current Rating 23A	Shell Material, Finish	Aluminum, Anodized Black Plated
Voltage - Rated 1000VAC Current Rating 23A	Contact Finish	Gold
Current Rating 23A	Features	-
	Voltage - Rated	1000VAC
Report errors?	Current Rating	23A
		Report errors?

MS3476A24-19S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3476A24-19S Payment Methods



















MS3476A24-19S Shipping Methods













If you have any question about MS3476A24-19S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com