

MS3476L8-98S Information

Heisener.com

Part Number MS3476L8-98S

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects
Circular Connectors

Description CONN PLUG 3POS INLINE SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3476L8-98S Specifications

Manufacturer Part NumberMS3476L8-98SManufacturerAmphenol Aerospace OperationsCategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-26482 Series IIConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert8-98Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VAC		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-26482 Series II Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert 8-98 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated Connectors, Interconnects Circular Connectors Hiller Connectors Aluminum, Miler Connectors Connectors, Interconnects Circular Connectors Bayonet Lock N (Normal) Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Features Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated	Manufacturer Part Number	MS3476L8-98S
Circular Connectors Package - Series Military, MIL-DTL-26482 Series II Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert 8-98 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated Military, MIL-DTL-26482 Series II Nilitary, MIL-DTL-26482 Series II Aluminer Series II Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-26482 Series II Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert 8-98 Shell Size, MIL Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - COVAC	Category	Connectors, Interconnects
Series Military, MIL-DTL-26482 Series II Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert 8-98 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated 600VAC		Circular Connectors
Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert 8-98 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated 600VAC	Package	-
Number of Positions Shell Size - Insert 8-98 Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated 600VAC	Series	Military, MIL-DTL-26482 Series II
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Contact Finish Gold Features Voltage - Rated 8-98 8-98 8-98 8-98 Environment Free Hanging (In-Line) Crimp Bayonet Lock N (Normal) Environment Resistant Shell Plated, Electroless Gold	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC	Number of Positions	3
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VAC	Shell Size - Insert	8-98
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated Bayonet Lock Bayonet Lock Bayonet Lock Bayonet Lock Aluminum N (Normal) Environment Resistant Aluminum, Nickel Plated, Electroless Gold 600VAC	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Aluminum, Nickel Plated, Electroless Gold 600VAC	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated 600VAC	Contact Finish	Gold
-	Features	-
	Voltage - Rated	600VAC
Current Rating 7.5A	Current Rating	7.5A
Report errors?		Report errors?

MS3476L8-98S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3476L8-98S Payment Methods



















MS3476L8-98S Shipping Methods













If you have any question about MS3476L8-98S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com