



MSM40A Information



For Reference Only

Part Number MSM40A Manufacturer Inventus Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 5.1V +/-12V 40W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3 FC3 F 40 A	G • 60 4 •
MSM40A	Specifications

Manufacturer Part Number MSM40A Manufacturer Inventus Power Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series MSM40 Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) 4A, 2A, 400mA Power (Watts) 40W Applications Medical Voltage - Isolation - Efficiency 73% Openation Tamparature 08C 508C	•	
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series MSM40 Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) 4A, 2A, 400mA Power (Watts) 40W Applications Medical Voltage - Isolation - Efficiency 73%	nufacturer Part Number	MSM40A
AC DC Converters Package - Series MSM40 Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) 4A, 2A, 400mA Power (Watts) 40W Applications Medical Voltage - Isolation - Efficiency 73%	nufacturer	Inventus Power
Package - Series MSM40 Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) 4A, 2A, 400mA Power (Watts) 40W Applications Medical Voltage - Isolation - Efficiency 73%	egory	Power Supplies - External/Internal (Off-Board)
Series MSM40 Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) 4A, 2A, 400mA Power (Watts) 40W Applications Medical Voltage - Isolation - Efficiency 73%		AC DC Converters
Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) 4A, 2A, 400mA Power (Watts) 40W Applications Medical Voltage - Isolation - Efficiency 73%	kage	-
Number of Outputs 3 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) 4A, 2A, 400mA Power (Watts) 40W Applications Medical Voltage - Isolation - Efficiency 73%	ies	MSM40
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) Applications Medical Voltage - Isolation Efficiency 73%	pe	Open Frame
Voltage - Output 1 Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Medical Voltage - Isolation Efficiency 5.1V 5.1V 5.1V 6.10 -12V -12V	mber of Outputs	3
Voltage - Output 2 Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Medical Voltage - Isolation - Efficiency 12V	ltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Voltage - Isolation Efficiency - 12V - 4A, 2A, 400mA 4W Medical Voltage - Isolation - 73%	ltage - Output 1	5.1V
Voltage - Output 4 - Current - Output (Max) 4A, 2A, 400mA Power (Watts) 40W Applications Medical Voltage - Isolation - Efficiency 73%	ltage - Output 2	12V
Current - Output (Max) 4A, 2A, 400mA Power (Watts) 40W Applications Medical Voltage - Isolation - Efficiency 73%	ltage - Output 3	-12V
Power (Watts) 40W Applications Medical Voltage - Isolation - Efficiency 73%	ltage - Output 4	-
Applications Medical Voltage - Isolation - Efficiency 73%	rrent - Output (Max)	4A, 2A, 400mA
Voltage - Isolation - Efficiency 73%	wer (Watts)	40W
Efficiency 73%	plications	Medical
·	ltage - Isolation	-
Organization Tomorrows 0°C 50°C	iciency	73%
Operating Temperature 0 C ~ 50 C	erating Temperature	0°C ~ 50°C
Features Universal Input	itures	Universal Input
Mounting Type Chassis Mount	unting Type	Chassis Mount
Size / Dimension 5.00" L x 3.00" W x 1.38" H (127.0mm x 76.2mm x 35.1mm)	e / Dimension	5.00" L x 3.00" W x 1.38" H (127.0mm x 76.2mm x 35.1mm)
Report error		Report errors?

MSM40A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MSM40A Payment Methods





















MSM40A Shipping Methods













If you have any question about MSM40A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com