

MSM6324 Information

Heisener.com

Part Number MSM6324 Manufacturer Inventus Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 24V 60W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MSM6324 Specifications

Manufacturer Part Number MSM6324 Manufacturer Inventus Power Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series MSM63 Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 60W Applications Medical Voltage - Isolation - Efficiency 80% Operating Temperature 0°C ~ 50°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.92" H (101.6mm x 50.8mm x 23.3mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series MSM63 Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 60W Applications Medical Voltage - Isolation - Efficiency 80% Operating Temperature 0°C ~ 50°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.92" H (101.6mm x 50.8mm x 23.3mm)	Manufacturer Part Number	MSM6324
Package - Series MSM63 Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 60W Applications Medical Voltage - Isolation - Efficiency 80% Operating Temperature 0°C ~ 50°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.92" H (101.6mm x 50.8mm x 23.3mm)	Manufacturer	Inventus Power
Package - Series MSM63 Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 60W Applications Medical Voltage - Isolation - Efficiency 80% Operating Temperature 0°C ~ 50°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.92" H (101.6mm x 50.8mm x 23.3mm)	Category	Power Supplies - External/Internal (Off-Board)
Series MSM63 Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 60W Applications Medical Voltage - Isolation - Efficiency 80% Operating Temperature 0°C ~ 50°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.92" H (101.6mm x 50.8mm x 23.3mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 60W Applications Medical Voltage - Isolation - Efficiency 80% Operating Temperature 0°C ~ 50°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.92" H (101.6mm x 50.8mm x 23.3mm)	Package	-
Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 60W Applications Medical Voltage - Isolation - Efficiency 80% Operating Temperature 0°C ~ 50°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.92" H (101.6mm x 50.8mm x 23.3mm)	Series	MSM63
Voltage - Input 100 ~ 240 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 60W Applications Medical Voltage - Isolation - Efficiency 80% Operating Temperature 0°C ~ 50°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.92" H (101.6mm x 50.8mm x 23.3mm)	Туре	Open Frame
Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 60W Applications Medical Voltage - Isolation - Efficiency 80% Operating Temperature 0°C ~ 50°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.92" H (101.6mm x 50.8mm x 23.3mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 Current - Output (Max) Power (Watts) Applications Medical Voltage - Isolation - Efficiency Operating Temperature Features Universal Input Mounting Type Size / Dimension - Current - Output (Max) - Current - Output (Max) - 60W Additable Additable Chassis Mount - Chassis Mount 4.00" L x 2.00" W x 0.92" H (101.6mm x 50.8mm x 23.3mm)	Voltage - Input	100 ~ 240 VAC
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 60W Applications Medical Voltage - Isolation - Efficiency 80% Operating Temperature 0°C ~ 50°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.92" H (101.6mm x 50.8mm x 23.3mm)	Voltage - Output 1	24V
Voltage - Output 4 Current - Output (Max) 2.5A Power (Watts) 60W Applications Medical Voltage - Isolation - Efficiency 80% Operating Temperature 0°C ~ 50°C Features Universal Input Mounting Type Chassis Mount Size / Dimension - Current - Output (Max) 2.5A Power (Watts) 60W Addical - Universal Input Chassis Mount 4.00" L x 2.00" W x 0.92" H (101.6mm x 50.8mm x 23.3mm)	Voltage - Output 2	-
Current - Output (Max) 2.5A Power (Watts) Applications Medical Voltage - Isolation - Efficiency 80% Operating Temperature 0°C ~ 50°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 2.5A 2.5A 2.5A 60W Medical - Universal Input Chassis Mount 4.00" L x 2.00" W x 0.92" H (101.6mm x 50.8mm x 23.3mm)	Voltage - Output 3	-
Power (Watts) 60W Applications Medical Voltage - Isolation - Efficiency 80% Operating Temperature 0°C ~ 50°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.92" H (101.6mm x 50.8mm x 23.3mm)	Voltage - Output 4	-
ApplicationsMedicalVoltage - Isolation-Efficiency 80% Operating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ FeaturesUniversal InputMounting TypeChassis MountSize / Dimension $4.00^{\circ}\text{L x } 2.00^{\circ}\text{W x } 0.92^{\circ}\text{H } (101.6 \text{mm x } 50.8 \text{mm x } 23.3 \text{mm})$	Current - Output (Max)	2.5A
Voltage - Isolation - Efficiency 80% Operating Temperature 0°C ~ 50°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.92" H (101.6mm x 50.8mm x 23.3mm)	Power (Watts)	60W
Efficiency 80% Operating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ Features Universal Input Mounting Type Chassis Mount Size / Dimension $4.00^{\circ}\text{L} \times 2.00^{\circ}\text{W} \times 0.92^{\circ}\text{H} (101.6\text{mm} \times 50.8\text{mm} \times 23.3\text{mm})$	Applications	Medical
Operating Temperature 0°C ~ 50°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.92" H (101.6mm x 50.8mm x 23.3mm)	Voltage - Isolation	-
Features Universal Input Mounting Type Chassis Mount Size / Dimension Universal Input Chassis Mount 4.00" L x 2.00" W x 0.92" H (101.6mm x 50.8mm x 23.3mm)	Efficiency	80%
Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.92" H (101.6mm x 50.8mm x 23.3mm)	Operating Temperature	0°C ~ 50°C
Size / Dimension 4.00" L x 2.00" W x 0.92" H (101.6mm x 50.8mm x 23.3mm)	Features	Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	4.00" L x 2.00" W x 0.92" H (101.6mm x 50.8mm x 23.3mm)
		Report errors?

MSM6324 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MSM6324 Payment Methods



















MSM6324 Shipping Methods













If you have any question about MSM6324, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com