

# **MSMP15015F**

uote

### **MSMP15015F** Information

	Part Number Manufacturer Category Description Package	Inventus Power Power Supplies - External/Internal (Off-Board) AC DC Converters AC/DC CONVERTER 15V 150W	
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Qu

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **MSMP15015F** Specifications

Manufacturer Inventus Power   Power Supplies - External/Internal (Off-Board)   AC DC Converters   Package   Package   Series   MSMP150   Symposition   Open Frame   Voltage - Input   Voltage - Output 1   00 ~ 240 VAC   Voltage - Output 2   1   Voltage - Output 3   2   Voltage - Output 4   3   Voltage - Output 5   3   Voltage - Output 4   -   Voltage - Solation   -   Voltage - Isolation   -   Voltage - Isolation   -   Voltage - Isolation   -			
CategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesMSMP150Spen FrameOpen FrameNumber of Outputs1Voltage - Input100 ~ 240 VACVoltage - Output 100 ~ 240 VACVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Voltage - Output 7-Voltage - Output 8-Voltage - Output 9-Voltage - Output 4-Output 9-Power (Watts)-Applications-Voltage - Isolation-Poreating TemperatureOfC ~ 70°C (With Derating)Poreating Temperature-FeaturesAdjustable Output, PFC, Standby Output, Universal InputFeatures-Size / Dimension-Size / Dimension-Size / Dimension-Size / Dimension-Size / Dimension-Power 10-Size / Dimension-Size / Dimensio	Manufacturer Part Number	MSMP15015F	
AC DC Converters   Package -   Series MSMP150   Type Open Frame   Number of Outputs 1   Voltage - Input 100 ~ 240 VAC   Voltage - Output 1 15V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 10A   Power (Watts) 150W   Applications Medical   Voltage - Isolation -   Efficiency 83%   Operating Temperature O°C ~ 0°C (With Derating)   Features Adjustable Output, PFC, Standby Output, Universal Input   Mounting Type Chassis Mount	Manufacturer	Inventus Power	
Package-SeriesMSMP150TypeOpen FrameNumber of Outputs1Voltage - Input100 ~ 240 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 410AVoltage - Output 410APower (Wats)15WVoltage - Isolation-Voltage - Isolation-Portige - Solation-Efficiency83%Operating TemperatureAdjustable Output, PFC, Standby Output, Universal InputFeaturesAdjustable Output, PFC, Standby Output, Universal InputSize / Dimension7.0° L x 4.50° W x 1.70° H (177.8m x 114.3mm x 43.2mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series MSMP150   Type Open Frame   Number of Outputs 1   Voltage - Input 100 ~ 240 VAC   Voltage - Output 1 15V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 10A   Power (Watts) 150W   Applications Medical   Voltage - Isolation -   Efficiency 83%   Operating Temperature Adjustable Output, PFC, Standby Output, Universal Input   Mounting Type Chassis Mount   Size / Dimension 7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)		AC DC Converters	
Type Open Frame   Number of Outputs 1   Voltage - Input 100 ~ 240 VAC   Voltage - Output 1 15V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Voltage - Solation 10A   Voltage - Isolation -   Voltage - Isolation -   Voltage - Isolation -   Voltage - Isolation -   Voltage - Solation -   Voltage - Solation -   Voltage - Solation -   Voltage - Solation -   Voltage - Sola	Package	-	
Number of Outputs 1   Voltage - Input 100 ~ 240 VAC   Voltage - Output 1 15V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 10A   Power (Watts) 150W   Applications Medical   Voltage - Isolation -   Efficiency 83%   Operating Temperature O°C ~ 70°C (With Derating)   Features Adjustable Output, PFC, Standby Output, Universal Input   Mounting Type Chassis Mount   Size / Dimension 7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Series	MSMP150	
Voltage - Input 100 ~ 240 VAC   Voltage - Output 1 15V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 10A   Power (Watts) 150W   Applications Medical   Voltage - Isolation -   Efficiency 83%   Operating Temperature 0°C ~ 70°C (With Derating)   Features Adjustable Output, PFC, Standby Output, Universal Input   Size / Dimension 7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Туре	Open Frame	
Voltage - Output 1 15V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 10A   Power (Watts) 150W   Applications Medical   Voltage - Isolation -   Efficiency 83%   Operating Temperature O°C ~ 70°C (With Derating)   Features Adjustable Output, PFC, Standby Output, Universal Input   Mounting Type Chassis Mount   Size / Dimension 7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Number of Outputs	1	
Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 10A   Power (Watts) 150W   Applications Medical   Voltage - Isolation -   Efficiency 83%   Operating Temperature 0°C ~ 70°C (With Derating)   Features Adjustable Output, PFC, Standby Output, Universal Input   Mounting Type Chassis Mount   Size / Dimension 7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Voltage - Input	100 ~ 240 VAC	
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)10APower (Watts)150WApplicationsMedicalVoltage - Isolation-Efficiency83%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Voltage - Output 1	15V	
Voltage - Output 4-Current - Output (Max)10APower (Watts)150WApplicationsMedicalVoltage - Isolation-Efficiency83%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Standby Output, Universal InputMounting Type7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Voltage - Output 2	-	
Current - Output (Max) 10A   Power (Watts) 150W   Applications Medical   Voltage - Isolation -   Efficiency 83%   Operating Temperature 0°C ~ 70°C (With Derating)   Features Adjustable Output, PFC, Standby Output, Universal Input   Mounting Type Chassis Mount   Size / Dimension 7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Voltage - Output 3	-	
Power (Watts)150WApplicationsMedicalVoltage - Isolation-Efficiency83%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Voltage - Output 4	-	
ApplicationsMedicalVoltage - Isolation-Efficiency83%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Current - Output (Max)	10A	
Voltage - Isolation-Efficiency83%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Power (Watts)	150W	
Efficiency83%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Applications	Medical	
Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Voltage - Isolation	-	
FeaturesAdjustable Output, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Efficiency	83%	
Mounting Type Chassis Mount   Size / Dimension 7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Operating Temperature	$0^{\circ}$ C ~ $70^{\circ}$ C (With Derating)	
Size / Dimension 7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Features	Adjustable Output, PFC, Standby Output, Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	
		Report errors?	

#### **MSMP15015F** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### **MSMP15015F** Payment Methods



## MSMP15015F Shipping Methods



If you have any question about MSMP15015F, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com