

# **MSMP25024F**

Juote

### **MSMP25024F Information**

		Inventus Power Power Supplies - External/Internal (Off-Board)	
	Description Package	AC DC Converters AC/DC CONVERTER 24V 250W	
	-	For the pricing/inventory/lead time, please contact us	<b>11</b> 308
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Q

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **MSMP25024F** Specifications

Manufacturer         Inventus Power           Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package           Series           Series           MSMP250           Sympo Open Frame           Voltage - Input           Soft - 264 VAC           Voltage - Output 1           Soft - 264 VAC           Voltage - Output 2           Voltage - Output 3           Soft - 264 VAC           Voltage - Output 4           Soft - 264 VAC           Voltage - Output 1           Soft - 264 VAC           Voltage - Output 2           Soft - 264 VAC           Voltage - Output 3           Soft - 264 VAC           Voltage - Output 4           Soft - 264 VAC           Voltage - Output 4           Soft - 264 VAC           Voltage - Output 4           Soft - 260 VOLT           Voltage - Output 4           Soft - 264 VAC           Voltage - Output 4           Soft - 265 VOLT           Voltage - Soft - 260 VOLT           Volta	_			
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         MSMP250           Speries         MSMP250           Voltage Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Voltage - Output 5         -           Voltage - Output 6         -           Voltage - Output 7         -           Voltage - Output 8         -           Voltage - Output 9         -           Voltage - Output 4         -           Current - Output (Max)         10.5A           Power (Watts)         250W (350W Forced Air)           Applications         -           Voltage - Isolation         -           Efficiency         88%           Operating Temperature         OrC ~70°C (With Derating)           Operating Temperature         Adjustable Output, PFC, Standby Output, Universal Input           Features         Adjustable Output 7.50° H (203.2mm x 127.0mm x 38.1mm)	Manufacturer Part Number	MSMP25024F		
AC DC ConvertersPackage-SeriesMSMP250TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output 4-Current - Output (Max)10.5APower (Watts)250W (350W Forced Air)Voltage - Isolation-Efficiency88%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Standby Output, Universal InputKounting Type6.00° L x 5.00° W x 1.50° H (203.2mm x 127.0mm x 38.1mm)	Manufacturer	Inventus Power		
Package-SeriesMSMP250TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 4-Voltage - Output 450W (350W Forced Air)Power (Watts)SOW (350W Forced Air)Voltage - Isolation-Efficiency8%Operating TemperatureO'C ~ 70°C (With Derating)FeaturesAjustable Output, PFC, Standby Output, Universal InputSize / Dimension8.00" L x 5.00" W x 1.50" H (203.2mm x 127.0mm x 38.1mm)	Category	Power Supplies - External/Internal (Off-Board)		
Series         MSMP250           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10.5A           Power (Watts)         250W (350W Forced Air)           Applications         Medical           Voltage - Isolation         -           Efficiency         88%           Operating Temperature         Orc ~ 70°C (With Derating)           Features         Adjustable Output, PFC, Standby Output, Universal Input           Mounting Type         Story W x 1.50" H (203.2mm x 127.0mm x 38.1mm)		AC DC Converters		
Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Voltage - Soluput (Max)         10.5A           Power (Watts)         250W (350W Forced Air)           Applications         -           Voltage - Isolation         -           Voltage - Isolation         -           Efficiency         0°C ~ 70°C (With Derating)           Operating Temperature         Adjustable Output, PFC, Standby Output, Universal Input           Mounting Type         Chasis Mount           Size / Dimension         80°C " X 50°C "W x 1.50° "H (203.2	Package	-		
Number of Outputs         I           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10.5A           Power (Watts)         250W (350W Forced Air)           Applications         Medical           Voltage - Isolation         -           Efficiency         88%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, PFC, Standby Output, Universal Input           Mounting Type         Kasis Mount           Size / Dimension         8.0°' L x 5.00'' W x 1.50'' H (203.2mm x 127.0mm x 38.1mm)	Series	MSMP250		
Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10.5A           Power (Watts)         250W (350W Forced Air)           Applications         Medical           Voltage - Isolation         -           Efficiency         88%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         8.00" L x 5.00" W x 1.50" H (203.2mm x 127.0mm x 38.1mm)	Туре	Open Frame		
Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10.5A           Power (Watts)         250W (350W Forced Air)           Applications         Medical           Voltage - Isolation         -           Efficiency         88%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, PFC, Standby Output, Universal Input           Mounting Type         Saw Mount           Size / Dimension         8.00" L x 5.00" W x 1.50" H (203.2mm x 127.0mm x 38.1mm)	Number of Outputs	1		
Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)10.5APower (Watts)250W (350W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency88%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Standby Output, Universal InputMounting TypeS.00" L x 5.00" W x 1.50" H (203.2mm x 127.0mm x 38.1mm)	Voltage - Input	85 ~ 264 VAC		
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)10.5APower (Watts)250W (350W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency88%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension8.00" L x 5.00" W x 1.50" H (203.2mm x 127.0mm x 38.1mm)	Voltage - Output 1	24V		
Voltage - Output 4-Current - Output (Max)10.5APower (Watts)250W (350W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency88%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Standby Output, Universal InputMounting Type6.00" L x 5.00" W x 1.50" H (203.2mm x 127.0mm x 38.1mm)	Voltage - Output 2	-		
Current - Output (Max)10.5APower (Watts)250W (350W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency88%Operating Temperature0°C ~ 70°C (With Derating)PeaturesAdjustable Output, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension8.00" L x 5.00" W x 1.50" H (203.2mm x 127.0mm x 38.1mm)	Voltage - Output 3	-		
Power (Watts)250W (350W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency88%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension8.00" L x 5.00" W x 1.50" H (203.2mm x 127.0mm x 38.1mm)	Voltage - Output 4	-		
ApplicationsMedicalVoltage - Isolation-Efficiency88%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension8.00" L x 5.00" W x 1.50" H (203.2mm x 127.0mm x 38.1mm)	Current - Output (Max)	10.5A		
NoVoltage - Isolation-Efficiency88%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension8.00" L x 5.00" W x 1.50" H (203.2mm x 127.0mm x 38.1mm)	Power (Watts)	250W (350W Forced Air)		
Efficiency88%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension8.00" L x 5.00" W x 1.50" H (203.2mm x 127.0mm x 38.1mm)	Applications	Medical		
Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension8.00" L x 5.00" W x 1.50" H (203.2mm x 127.0mm x 38.1mm)	Voltage - Isolation	-		
FeaturesAdjustable Output, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension8.00" L x 5.00" W x 1.50" H (203.2mm x 127.0mm x 38.1mm)	Efficiency	88%		
Mounting TypeChassis MountSize / Dimension8.00" L x 5.00" W x 1.50" H (203.2mm x 127.0mm x 38.1mm)	Operating Temperature	$0^{\circ}$ C ~ $70^{\circ}$ C (With Derating)		
Size / Dimension         8.00" L x 5.00" W x 1.50" H (203.2mm x 127.0mm x 38.1mm)	Features	Adjustable Output, PFC, Standby Output, Universal Input		
	Mounting Type	Chassis Mount		
Report errors?	Size / Dimension	8.00" L x 5.00" W x 1.50" H (203.2mm x 127.0mm x 38.1mm)		
		Report errors		

#### **MSMP25024F** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# **MSMP25024F** Payment Methods



# MSMP25024F Shipping Methods



If you have any question about MSMP25024F, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com