

# **MSRTA40080(A)**

# MSRTA40080(A) Information

WWW.there Cont	MSRTA40080(A) GeneSiC Semiconductor Discrete Semiconductor Products Diodes - Rectifiers - Arrays DIODE MODULE 800V 400A 3TOWER Three Tower For the pricing/inventory/lead time, please contact us	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# MSRTA40080(A) Specifications

Manufacturer     GeneSiC Semiconductor       Category     Discrete Semiconductor Products       Diodes - Rectifiers - Arrays     Diodes - Rectifiers - Arrays       Package     Three Tower       Series     -       Diode Configuration     1 Pair Common Cathode       Diode Type     Standard       Voltage - DC Reverse (Vr) (Max)     800V       Current - Average Rectified (Io) (per Diode)     400A (DC)       Voltage - Forward (Vf) (Max) @ If     1.2V @ 400A       Speed     Standard Recovery >500ns, > 200mA (Io)       Reverse Recovery Time (trr)     -       Current - Reverse Leakage @ Vr     25µA @ 600V       Operating Temperature - Junction     -55°C ~ 150°C       Mounting Type     Chassis Mount       Package / Case     Three Tower		
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - ArraysPackageThree TowerSeries-Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io) (per Diode)400A (DC)Voltage - Forward (Vf) (Max) @ If1.2V @ 400ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr25µA @ 600VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Manufacturer Part Number	MSRTA40080(A)
Diodes - Rectifiers - ArraysPackageThree TowerSeries-Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io) (per Diode)400A (DC)Voltage - Forward (Vf) (Max) @ If1.2V @ 400ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr25µA @ 600VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Manufacturer	GeneSiC Semiconductor
PackageThree TowerSeries-Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io) (per Diode)400A (DC)Voltage - Forward (Vf) (Max) @ If1.2V @ 400ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr25µA @ 600VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Category	Discrete Semiconductor Products
Series-Series-Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io) (per Diode)400A (DC)Voltage - Forward (Vf) (Max) @ If1.2V @ 400ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr25µA @ 600VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower		Diodes - Rectifiers - Arrays
Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io) (per Diode)400A (DC)Voltage - Forward (Vf) (Max) @ If1.2V @ 400ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr25µA @ 600VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Package	Three Tower
Diode TypeStandardDiode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io) (per Diode)400A (DC)Voltage - Forward (Vf) (Max) @ If1.2V @ 400ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr25µA @ 600VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Series	-
Voltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io) (per Diode)400A (DC)Voltage - Forward (Vf) (Max) @ If1.2V @ 400ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr25µA @ 600VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Diode Configuration	1 Pair Common Cathode
Current - Average Rectified (Io) (per Diode)400A (DC)Voltage - Forward (Vf) (Max) @ If1.2V @ 400ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr25µA @ 600VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If1.2V @ 400ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr25μA @ 600VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Voltage - DC Reverse (Vr) (Max)	800V
SpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr25μA @ 600VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Current - Average Rectified (Io) (per Diode)	400A (DC)
Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr25μA @ 600VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Voltage - Forward (Vf) (Max) @ If	1.2V @ 400A
Current - Reverse Leakage @ Vr25µA @ 600VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Speed	Standard Recovery >500ns, > 200mA (Io)
Operating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Reverse Recovery Time (trr)	-
Mounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Current - Reverse Leakage @ Vr	25µA @ 600V
Package / Case Three Tower   Supplier Device Package Three Tower	Operating Temperature - Junction	-55°C ~ 150°C
Supplier Device Package Three Tower	Mounting Type	Chassis Mount
	Package / Case	Three Tower
Report errors?	Supplier Device Package	Three Tower
		Report errors?

#### MSRTA40080(A) Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### MSRTA40080(A) Payment Methods



## MSRTA40080(A) Shipping Methods



If you have any question about MSRTA40080(A), please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com