

MT-7-12 Information

Heisener.com

Part Number MT-7-12

Manufacturer Signal Transformer Transformers

Category **Power Transformers**

Description XFRMR LAMINATED 7VA CHAS MOUNT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MT-7-12 Specifications

Manufacturer Part Number MT-7-12 Manufacturer Signal Transformer Category Transformers Package - Series MT Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 5V, 12V Current - Output (Max) 2.8A, 350mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap Yes Power - Max 7 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 93.70mm L x 49.20mm W Height - Seated (Max) 57.80mm Voltage - Isolation 2500Vrms		
CategoryTransformersPackage-SeriesMTTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)5V, 12VCurrent - Output (Max)2.8A, 350mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapYesPower - Max7 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension93.70mm L x 49.20mm WHeight - Seated (Max)57.80mm	Manufacturer Part Number	MT-7-12
Package - Series MT Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 5V, 12V Current - Output (Max) 2.8A, 350mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap Yes Power - Max 7 VA Mounting Type Chassis Mount Termination Style Size / Dimension 93.70mm L x 49.20mm W Height - Seated (Max)	Manufacturer	Signal Transformer
Package-SeriesMTTypeLaminated CoreVoltage - Primary115 VVoltage - Secondary (Full Load)5 V, 12 VCurrent - Output (Max)2.8A, 350mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapYesPower - Max7 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension93.70mm L x 49.20mm WHeight - Seated (Max)57.80mm	Category	Transformers
Series MT Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 5V, 12V Current - Output (Max) 2.8A, 350mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap Yes Power - Max 7VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 93.70mm L x 49.20mm W Height - Seated (Max) 57.80mm		Power Transformers
Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 5V, 12V Current - Output (Max) 2.8A, 350mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap Yes Power - Max 7 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 93.70mm L x 49.20mm W Height - Seated (Max) 57.80mm	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap Yes Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) 115V 2.8A, 350mA Single Single Yes Poual Yes 7 VA Solder, Quick Connect 93.70mm L x 49.20mm W 57.80mm	Series	MT
Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Single Yes Poual Chassis Mount Solder, Quick Connect 93.70mm L x 49.20mm W 57.80mm	Type	Laminated Core
Current - Output (Max) Primary Winding(s) Single Secondary Winding(s) Dual Center Tap Yes Power - Max 7 VA Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) 2.8A, 350mA 2.8A, 350mA Single Dual Yes Yes 7 VA 57.80mm	Voltage - Primary	115V
Primary Winding(s) Secondary Winding(s) Dual Center Tap Yes Power - Max 7 VA Mounting Type Chassis Mount Termination Style Size / Dimension Primary Winding(s) Single Yes Yes 7 VA 57 VA Solder, Quick Connect Size / Dimension 93.70mm L x 49.20mm W 57.80mm	Voltage - Secondary (Full Load)	5V, 12V
Secondary Winding(s)DualCenter TapYesPower - Max7 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension93.70mm L x 49.20mm WHeight - Seated (Max)57.80mm	Current - Output (Max)	2.8A, 350mA
Center TapYesPower - Max7 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension93.70mm L x 49.20mm WHeight - Seated (Max)57.80mm	Primary Winding(s)	Single
Power - Max Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 93.70mm L x 49.20mm W Height - Seated (Max) 57.80mm	Secondary Winding(s)	Dual
Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 93.70mm L x 49.20mm W Height - Seated (Max) 57.80mm	Center Tap	Yes
Termination Style Solder, Quick Connect Size / Dimension 93.70mm L x 49.20mm W Height - Seated (Max) 57.80mm	Power - Max	7 VA
Size / Dimension 93.70mm L x 49.20mm W Height - Seated (Max) 57.80mm	Mounting Type	Chassis Mount
Height - Seated (Max) 57.80mm	Termination Style	Solder, Quick Connect
	Size / Dimension	93.70mm L x 49.20mm W
Voltage - Isolation 2500Vrms	Height - Seated (Max)	57.80mm
	Voltage - Isolation	2500Vrms
Weight 1.7 lbs (771.1g)	Weight	1.7 lbs (771.1g)
Report errors?		Report errors?

MT-7-12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MT-7-12 Payment Methods





















MT-7-12 Shipping Methods













If you have any question about MT-7-12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com