

### MT226012 Information



For Reference Only

Part Number MT226012

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE DPDT 10A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **MT226012 Specifications**

Manufacturer Part Number         MT226012           Manufacturer         TE Connectivity Potter & Brumfield Relays           Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         MT, SCHRACK           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         -           Coil Voltage         12VAC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         10A           Switching Voltage         400VAC - Max           Turn On Voltage (Max)         9.6 VAC           Turn Off Voltage (Min)         4.8 VAC           Operate Time         15ms           Release Time         10ms           Features         Test Button           Mounting Type         Socketable           Termination Style         Plug In, 8 Pin (Octal)		
Relays Power Relays, Over 2 Amps  Package - Series MT, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 12VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 400VAC - Max Turn On Voltage (Max) 9.6 VAC Turn Off Voltage (Min) 4.8 VAC Operate Time 15ms Release Time 10ms Features Mounting Type Socketable	Manufacturer Part Number	MT226012
Package         -           Series         MT, SCHRACK           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         -           Coil Voltage         12VAC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         10A           Switching Voltage         400VAC - Max           Turn On Voltage (Max)         9.6 VAC           Turn Off Voltage (Min)         4.8 VAC           Operate Time         15ms           Release Time         10ms           Features         Test Button           Mounting Type         Socketable	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - MT, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 12VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 400VAC - Max Turn On Voltage (Max) 9.6 VAC Turn Off Voltage (Min) 4.8 VAC Operate Time 15ms Release Time 10ms Features Test Button Mounting Type Socketable	Category	Relays
SeriesMT, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage12VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage400VAC - MaxTurn On Voltage (Max)9.6 VACTurn Off Voltage (Min)4.8 VACOperate Time15msRelease Time10msFeaturesTest ButtonMounting TypeSocketable		Power Relays, Over 2 Amps
Relay Type General Purpose  Coil Type Non Latching  Coil Current - Coil Voltage 12VAC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 10A  Switching Voltage 400VAC - Max  Turn On Voltage (Max) 9.6 VAC  Turn Off Voltage (Min) 4.8 VAC  Operate Time 15ms  Release Time 10ms  Features Test Button  Mounting Type Socketable	Package	-
Coil Type Non Latching Coil Current - Coil Voltage 12VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 400VAC - Max Turn On Voltage (Max) 9.6 VAC Turn Off Voltage (Min) 4.8 VAC Operate Time 15ms Release Time 10ms Features Test Button Mounting Type Socketable	Series	MT, SCHRACK
Coil Current         -           Coil Voltage         12VAC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         10A           Switching Voltage         400VAC - Max           Turn On Voltage (Max)         9.6 VAC           Turn Off Voltage (Min)         4.8 VAC           Operate Time         15ms           Release Time         10ms           Features         Test Button           Mounting Type         Socketable	Relay Type	General Purpose
Coil Voltage 12VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 400VAC - Max Turn On Voltage (Max) 9.6 VAC Turn Off Voltage (Min) 4.8 VAC Operate Time 15ms Release Time 10ms Features Test Button Mounting Type Socketable	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  400VAC - Max  Turn On Voltage (Max)  9.6 VAC  Turn Off Voltage (Min)  4.8 VAC  Operate Time  15ms  Release Time  10ms  Features  Test Button  Mounting Type  Socketable	Coil Current	-
Contact Rating (Current)  Switching Voltage  400VAC - Max  Turn On Voltage (Max)  9.6 VAC  Turn Off Voltage (Min)  4.8 VAC  Operate Time  15ms  Release Time  10ms  Features  Test Button  Mounting Type  Socketable	Coil Voltage	12VAC
Switching Voltage 400VAC - Max  Turn On Voltage (Max) 9.6 VAC  Turn Off Voltage (Min) 4.8 VAC  Operate Time 15ms  Release Time 10ms  Features Test Button  Mounting Type Socketable	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  4.8 VAC  Operate Time  15ms  Release Time  10ms  Features  Test Button  Mounting Type  Socketable	Contact Rating (Current)	10A
Turn Off Voltage (Min)  Operate Time  15ms  Release Time  10ms  Features  Test Button  Mounting Type  Socketable	Switching Voltage	400VAC - Max
Operate Time15msRelease Time10msFeaturesTest ButtonMounting TypeSocketable	Turn On Voltage (Max)	9.6 VAC
Release Time 10ms Features Test Button Mounting Type Socketable	Turn Off Voltage (Min)	4.8 VAC
Features Test Button Mounting Type Socketable	Operate Time	15ms
Mounting Type Socketable	Release Time	10ms
	Features	Test Button
Termination Style Plug In, 8 Pin (Octal)	Mounting Type	Socketable
	Termination Style	Plug In, 8 Pin (Octal)
Report errors?		Report errors?

### MT226012 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **MT226012 Payment Methods**



















### MT226012 Shipping Methods













If you have any question about MT226012, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com