

MT226060 Information



For Reference Only

Part Number MT226060

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 10A 60V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MT226060 Specifications

Manufacturer Part Number MT226060 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series MT, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 60VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 400VAC - Max Turn On Voltage (Max) 48 VAC Turn Off Voltage (Min) 24 VAC Operate Time 15ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)		
Category Relays Power Relays, Over 2 Amps Package - Series MT, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 60VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 400VAC - Max Turn On Voltage (Max) 48 VAC Turn Off Voltage (Min) 24 VAC Operate Time 15ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Manufacturer Part Number	MT226060
Package - Series MT, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 60VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 400VAC - Max Turn On Voltage (Max) 48 VAC Turn Off Voltage (Min) 24 VAC Operate Time 15ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series MT, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 60VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 400VAC - Max Turn On Voltage (Max) 48 VAC Turn Off Voltage (Min) 24 VAC Operate Time 15ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Category	Relays
SeriesMT, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage60VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage400VAC - MaxTurn On Voltage (Max)48 VACTurn Off Voltage (Min)24 VACOperate Time15msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, 8 Pin (Octal)		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage60VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage400VAC - MaxTurn On Voltage (Max)48 VACTurn Off Voltage (Min)24 VACOperate Time15msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, 8 Pin (Octal)	Package	-
Coil TypeNon LatchingCoil Current-Coil Voltage60VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage400VAC - MaxTurn On Voltage (Max)48 VACTurn Off Voltage (Min)24 VACOperate Time15msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, 8 Pin (Octal)	Series	MT, SCHRACK
Coil Current - Coil Voltage 60VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 400VAC - Max Turn On Voltage (Max) 48 VAC Turn Off Voltage (Min) 24 VAC Operate Time 15ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Relay Type	General Purpose
Coil Voltage60VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage400VAC - MaxTurn On Voltage (Max)48 VACTurn Off Voltage (Min)24 VACOperate Time15msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, 8 Pin (Octal)	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 400VAC - Max Turn On Voltage (Max) 48 VAC Turn Off Voltage (Min) 24 VAC Operate Time 15ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style	Coil Current	-
Contact Rating (Current) Switching Voltage 400VAC - Max Turn On Voltage (Max) 48 VAC Turn Off Voltage (Min) 24 VAC Operate Time 15ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Coil Voltage	60VAC
Switching Voltage 400VAC - Max Turn On Voltage (Max) 48 VAC Turn Off Voltage (Min) 24 VAC Operate Time 15ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 48 VAC Turn Off Voltage (Min) 24 VAC Operate Time 15ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Contact Rating (Current)	10A
Turn Off Voltage (Min) 24 VAC Operate Time 15ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Switching Voltage	400VAC - Max
Operate Time 15ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Turn On Voltage (Max)	48 VAC
Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Turn Off Voltage (Min)	24 VAC
Features Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Operate Time	15ms
Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Release Time	10ms
Termination Style Plug In, 8 Pin (Octal)	Features	Test Button
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, 8 Pin (Octal)
L.		Report errors?

MT226060 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MT226060 Payment Methods





















MT226060 Shipping Methods













If you have any question about MT226060, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com